

QUIVOGNE

2,12 to 2,52 m



BDEM

**HYDRAULICALLY
SHIFTABLE**

SIDE MULCHER

PRODUCT FEATURES

- Working width 2,12 – 2,52 m
- For tractors from 40 – 60 HP
- PTO speed 540 rpm
- Y-blades
- Rear hood can be opened (for maintenance)

STANDARD FEATURES

- Three point floating linkage with floating connection rod
- Hydraulic side shift
- Inclination angle -75° / $+90^{\circ}$
- Inner positioned gearbox (540 rpm) with free wheel and PTO shaft
- Cardan shaft 1" 3/8 Z6
- Counter knives
- Adjustable side skids
- Adjustable rear roller \varnothing 140 mm

OPTIONS

- 2 lever distributor + oleopneumatic accumulator
- 2 lever distributor with teleflexible controls
- Oleopneumatic accumulator
- (Double) constant velocity PTO shaft
- Rear roller \varnothing 194 mm
- Increase left hand series
- Self levelling joint for left hand series
- Self levelling joint
- Hammer flails

BDEM

Model	Article Code	Working width (cm)	Cutting height (cm)	Cutting thickness with hammers (cm)	Y-blades / hammer flails (pcs.)	V-belts (pcs.)	Required power (HP)	Weight (kg)
BDEM 210	M 4285 010	212	2 - 8	4*	56 / 28	4	40 - 60	670
BDEM 225	M 4285 011	221	2 - 8	4*	64 / 32	4	45 - 60	692
BDEM 250	M 4285 011	252	2 - 8	4*	80 / 40	4	50 - 60	770

* with hammer flails

OPTIONS FOR BDEM	For model	Article Code	Weight (kg)
2 lever distributor + oleopneumatic accumulator		E 4285 500	
2 lever distributor with teleflexible controls		E 4285 501	
Oleopneumatic accumulator		E 4285 503	
Constant velocity PTO shaft		E 4285 504	
Double constant velocity PTO shaft		E 4285 505	
Rear roller Ø 194 mm <i>instead of Ø 140 mm</i>	BDEM 210	E 4285 510	
	BDEM 225	E 4285 511	
	BDEM 250	E 4285 512	
Increase left hand series		E 4285 506	
Self levelling joint for left hand series		E 4285 507	
Self levelling joint		E 4285 508	
Hammer flails <i>instead of Y-blades</i>		E 4285 509	
Hammer flails <i>instead of Y-blades</i>		E 4285 511	

Note: For the operation of the side mulcher BDEM the tractor has to be equipped with 2 double-acting control units.



QUIVOGNE CEE GmbH
Ungargasse 32/Top 1
A-1030 Vienna
AUSTRIA

Phone: + 43 699 1997 1936
Fax: + 43 1997 1935 10
Email: info@quivogne.at

www.quivogne.info