

QUIVOGNE

1,82 to 2,49 m



BDHM

RIGID

SIDE MULCHER

PRODUCT FEATURES

- Working width 1,82 – 2,49 m
- For tractors from 80 – 120 HP
- Double welded chassis
- PTO speed 540 rpm
- Hammer flails
- Rear hood can be opened (for maintenance)

STANDARD FEATURES

- Three point floating linkage Cat. 2
- Hydraulic side shift
- Inclination angle -60° / $+90^{\circ}$
- Inner positioned gearbox (540 rpm) with free wheel and PTO shaft
- Cardan shaft 1"3/8 Z6
- Counter knives
- Adjustable rear roller

OPTIONS

- Double constant velocity PTO shaft
- Side skids
- Shockproof hydraulic safety valves
- Chains for stone protection in front

BDHM

Model	Article Code	Working width (cm)	Cutting height (cm)	Cutting thickness with hammers (cm)	Hammer flails (pcs.)	V-belts (pcs.)	Required power (HP)	Weight (kg)
BDHM 180	M 4269 010	182	3 - 8	5	16	4	80 - 120	980
BDHM 200	M 4269 011	200	3 - 8	5	18	4	80 - 120	1.020
BDHM 220	M 4269 012	219	3 - 8	5	20	4	90 - 120	1.070
BDHM 250	M 4269 013	249	3 - 8	5	22	4	90 - 120	1.120

OPTIONS FOR BDHM	For model	Article Code	Weight (kg)
Stone protection chains in front	BDHM 180	E 4260 510	
	BDHM 200	E 4260 511	
	BDHM 220	E 4260 512	
	BDHM 250	E 4260 513	
Shockproof hydraulic safety valves		E 4260 500	
Side skids		E 4260 501	
Double constant velocity PTO shaft		E 4260 502	

Note: For the operation of the side mulcher BDHM the tractor has to be equipped with 2 double-acting control units.



QUIVOGNE CEE GmbH
Ungargasse 32/Top 1
A-1030 Vienna
AUSTRIA

Phone: + 43 699 1997 1936
Fax: + 43 1997 1935 10
Email: info@quivogne.at

www.quivogne.info