

**QUIVOGNE**

1,82 to 2,49 m



# BDHM XL

**HYDRAULICALLY  
SHIFTABLE**

## SIDE MULCHER

### PRODUCT FEATURES

- Working width 1,82 – 2,49 m
- For tractors from 80 – 120 HP
- PTO speed 540 rpm
- Double welded chassis
- Hammer flails
- Rear hood can be opened (for maintenance)

### STANDARD FEATURES

- Three point floating linkage Cat. 2
- Hydraulic side shift
- Inclination angle  $-60^{\circ}$  /  $+90^{\circ}$
- Outer positioned gearbox (540 rpm) with free wheel and PTO shaft
- Cardan shaft 1" 3/8 Z6
- Counter knives
- Adjustable rear roller

### OPTIONS

- Double constant velocity PTO shaft
- Side skids
- Shockproof hydraulic safety valves
- Chains for stone protection in front

## BDHM XL

Model	Article Code	Working width (cm)	Cutting height (cm)	Cutting thickness with hammers (cm)	Hammer flails (pcs.)	V-belts (pcs.)	Required power (HP)	Weight (kg)
<b>BDHM XL 180</b>	M 4284 010	182	3 - 8	5	16	4	80 - 120	990
<b>BDHM XL 200</b>	M 4284 011	200	3 - 8	5	18	4	80 - 120	1.030
<b>BDHM XL 220</b>	M 4284 012	219	3 - 8	5	20	4	90 - 120	1.070
<b>BDHM XL 250</b>	M 4284 013	249	3 - 8	5	22	4	90 - 120	1.110

OPTIONS FOR BDHM XL	For model	Article Code	Weight (kg)
<b>Stone protection chains in front</b>	BDHM XL 180	E 4284 510	
	BDHM XL 200	E 4284 511	
	BDHM XL 220	E 4284 512	
	BDHM XL 250	E 4284 513	
<b>Shockproof hydraulic safety valves</b>		E 4284 500	
<b>Side skids</b>		E 4284 501	
<b>Double constant velocity PTO shaft</b>		E 4284 502	

Note: For the operation of the side mulcher BDHM XL the tractor has to be equipped with 2 double-acting control units.



QUIVOGNE CEE GmbH  
Ungargasse 32/Top 1  
A-1030 Vienna  
AUSTRIA

Phone: + 43 699 1997 1936  
Fax: + 43 1997 1935 10  
Email: info@quivogne.at

[www.quivogne.info](http://www.quivogne.info)