



**QUIVOGNE**

Ø565

Ø450

4 - 6 m

# DISKATOR S

**HYDRAULICALLY  
FOLDABLE**

## COMPACT DISC HARROW MOUNTED / 2 ROWS

### PRODUCT FEATURES

- Working width 4 | 5 | 6 m
- For tractors 120 - 250 HP
- Working depth 3 - 15 cm (adjustable via the trailing roller)
- Sturdy framework with two rows, frame profile 250 x 250 mm
- Two staged disc rows with effective disc distance of 125 mm
- Disc spacing in each row 250 mm
- Transport width 2,5 m
- Transport height 4 m (working width 6 m with tyres 445/45R19,5)

### STANDARD FEATURES

- Three point linkage Cat. 3
- Individual suspended jagged discs Ø 450 x 4,5 or Ø 560 x 5 mm with maintenance free double tapered roller bearings and rubber stone protection elements
- Combination: comb harrow (tines Ø 10 mm) after the rear disc section and a Z-roller Ø 500 mm
- 2 side deflector boards (left/right)
- 2 stands

### OPTIONS

- Variety of trailing rollers
- Catch crop seeder COMBIDRILL
- Warning plates and lighting
- Depth wheels 400/60x15,5
- Hydraulic trailing roller adjustment
- Drawbar with drawbar eye Ø 50 mm + rear chassis with wheels 445/45R19,5
- Longer drawbar

### FIELD OF APPLICATION / ADVANTAGES

- The universal implement for soil tillage (working depth 3 to 15 cm).
- Intense and homogeneous mixing of soil and organic matter, optimal seed bed preparation.
- Optimal soil mixing via the tine harrow and direct reconsolidation via the trailing roller ensures quick rotting of the residues and only low loss of moisture.
- Adaption to the soil contour through individual suspended discs.
- Recommended working speed: 15-18 km/h







## DISKATOR S: with notched discs Ø 560 x 5 mm and Z-roller Ø 500 mm

Model	Article Code	Working width (cm)	Discs (pcs.)	Required power (HP)	Weight (kg)
DISKATOR S 400/5H	M 1320 020	400	32	120 - 160	2.618
DISKATOR S 500/5H	M 1320 021	500	40	150 - 200	3.078
DISKATOR S 600/5H	M 1320 022	600	48	180 - 250	3.470

## DISKATOR S: with notched discs Ø 450 x 4,5 mm and Z-roller Ø 500 mm

Model	Article Code	Working width (cm)	Discs (pcs.)	Required power (HP)	Weight (kg)
DISKATOR S 400/4H	M 1320 010	400	32	120 - 160	2.458
DISKATOR S 500/4H	M 1320 011	500	40	150 - 200	2.878
DISKATOR S 600/4H	M 1320 012	600	48	180 - 250	3.230


OPTIONS FOR DISKATOR S HYDRAULICALLY FOLDABLE		Article Code	Weight (kg)
	<b>Warning plates and lighting</b> (1 pair)	E 1320 500	12
	<b>Catch crop seeder COMBIDRILL</b> with electric fan drive	E 1320 501	
	<b>Hydraulic trailing roller adjustment</b>	E 1320 502	60
	<b>Drawbar with drawbar eye Ø 50 mm + rear chassis with tyres 445/45R19,5</b> (1 pair, + 1DW)	E 1320 502	835
	<b>Depth wheels 400/60x15,5</b> (1 pair) chassis necessary	E 1320 504	mechanically adjustable
		E 1320 505	hydraulically adjustable
	<b>Longer drawbar with drawbar eye Ø 50 mm</b> necessary for depth wheels	E 1320 502	
	<b>Roller with working width 3 m and transport width 3,2 m</b> instead of transport width 3 m	E 1320 506	



**TRAILING ROLLERS FOR DISKATOR S HYDRAULICALLY FOLDABLE**

**Article  
Code**

**Working width (cm)**



**L-roller Ø 600 mm**  
*with scrapers*

E 1320 520 400

E 1320 521 500

E 1320 522 600



**T-roller Ø 600 mm**  
*with scrapers*

E 1320 530 400

E 1320 531 500

E 1320 532 600



**U-roller Ø 600 mm**  
*with scrapers*

E 1320 540 400

E 1320 541 500

E 1320 542 600



**LAMFLEX-roller Ø 520 mm**

E 1320 550 400

E 1320 551 500

E 1320 552 600



**ROLLPRO-roller Ø 600 mm**  
*with scrapers*

E 1320 560 400

E 1320 561 500

E 1320 562 600



**FARMFLEX-roller Ø 586 mm**  
*with scrapers*

E 1320 570 400

E 1320 571 500

E 1320 572 600



**ROLLSTEEL-roller Ø 600 mm**  
*with scrapers*

E 1320 580 400

E 1320 581 500

E 1320 582 600



QUIV OGNE