



QUIVOGNE



Ø565



6 - 12 m



# DISKATOR SL

HYDRAULICALLY  
FOLDABLE

## HEAVY COMPACT DISC HARROW TRAILED / 2 ROWS

### PRODUCT FEATURES

- Working width 6 - 12 m
- For tractors 210 - 600 HP
- Working depth 3 - 15 cm (adjustable via the trailing roller)
- Sturdy framework with two rows, frame profile 300 x 300 mm
- Two staged disc rows with effective disc distance of 125 mm
- Disc spacing in each row 250 mm
- Transport width 3m
- Transport height: from 3,9 m (working width 6 m with tyres 550/60x22,5, without pendulum system, with tube roller.) The transport height increases with pendulum system, tyres 680/55x26,5 and different roller type.

### STANDARD FEATURES

- Hydraulically adjustable drawbar with ball joint drawbar eye Ø 51 mm
- Individual suspended notched discs Ø 560 x 5 mm with maintenance free double tapered roller bearings and rubber stone protection elements
- Chassis with tyres 550/60x 22,5 90 mm square axle with 10 bolts
- Combination: Comb harrow (tines Ø 10 mm) after the rear disc section and tube roller Ø 540 mm
- Working width 10 and 12 m: pendulum system for better soil contour adaptation (not compatible with comb harrow)
- 2 side deflector boards (left/right)
- 2 stands

### OPTIONS

- Variety of rollers
- Scharmüller K80 ball trailer coupling
- Catch crop seeder COMBIDRILL
- Hydraulic trailing roller adjustment
- Warning plates and lighting
- Pneumatic brake
- Pendulum system
- Tyres 680/55 x 26,5 instead of 550/60 x 22,5

### FIELD OF APPLICATION / ADVANTAGES

- Our heavy compact disc harrow for mixing of residues and seedbed preparation.
- Perfect soil cultivation through notched discs in 3 to 15 cm working depth, adjustable via the trailing roller.
- Optimal soil mixing via the tine harrow and direct reconsolidation via the trailing roller ensures quick rotting of the residues and only low loss of moisture.
- Adaption to the soil contour through individual suspended discs.
- High efficiency through high working speed and low wear cost.
- Recommended working speed: 15-18 km/h



Drawbar with ball joint drawbar eye Ø 51 mm (standard)



Pendulum system at 10 and 12m working width



Chassis








Comb harrow + side deflector boards (standard)

## DISKATOR SL: with notched discs Ø 560 x 5 mm, comb harrow and tube roller Ø 540 mm

Model	Article Code	Working width (cm)	Discs (pcs.)	Required power (HP)	Weight (kg)
<b>DISKATOR SL 600</b>	M 1280 010	600	48	210 - 300	8.538
<b>DISKATOR SL 700</b>	M 1280 011	700	56	245 - 350	9.018
<b>DISKATOR SL 800</b>	M 1280 012	800	64	280 - 400	9.506
<b>DISKATOR SL 900</b>	M 1280 013	900	72	315 - 450	10.200
<b>DISKATOR SL 1000*</b>	M 1280 014	1.000	80	350 - 500	10.458
<b>DISKATOR SL 1200*</b>	M 1280 015	1.200	96	420 - 600	10.926

\* Without comb harrow, as not compatible with pendulum system.

OPTIONS FOR DISKATOR SL		Article Code	Weight (kg)
	<b>Warning plates and lighting</b> (1 pair)	E 1280 500	12
	<b>Pneumatic brake</b>	E 1280 501	
	<b>Tyres 680/55 x 26,5 instead of 550/60x22,5</b> (1 pair)	E 1280 502	
	<b>Scharmüller K80 ball trailer coupling</b> with adapter, instead of standard coupling	E 1280 503	5
	<b>Catch crop seeder COMBIDRILL 800 - 1600 Liters</b> with hydraulic fan drive	E 1280 504	
	<b>Pendulum system for better soil contour adaptation</b> for DISKATOR SL 600, 700, 800, 900 not compatible with comb harrow, machine is delivered without comb harrow	E 1280 505	
	<b>Discs mounted in X-shape instead of V-shape</b>	E 1280 507	
	<b>Hydraulic trailing roller adjustment (+ 1DW)</b>	E 1280 507	




# QUIVOGNE

**TRAILING ROLLERS FOR DISKATOR SL**
**Article  
Code**
**Working width (cm)**

**Z-roller Ø 500 mm,**  
*with comb harrow, tines Ø 10 mm*

E 1280 520	600
E 1280 521	700
E 1280 522	800
E 1280 523	900
E 1280 524	1.000
E 1280 525	1.200


**L-roller Ø 600 mm**  
*with scrapers  
without comb harrow*

E 1280 530	600
E 1280 531	700
E 1280 532	800
E 1280 533	900
E 1280 534	1.000
E 1280 535	1.200


**T-roller Ø 600 mm**  
*with scrapers  
without comb harrow*

E 1280 540	600
E 1280 541	700
E 1280 542	800
E 1280 543	900
E 1280 544	1.000
E 1280 545	1.200


**U-roller Ø 600 mm**  
*with scrapers  
without comb harrow*


E 1280 550	600
E 1280 551	700
E 1280 552	800
E 1280 553	900
E 1280 554	1.000
E 1280 555	1.200


**LAMFLEX-roller Ø 520 mm**  
*without comb harrow*

E 1280 560	600
E 1280 561	700
E 1280 562	800
E 1280 563	900
E 1280 564	1.000
E 1280 565	1.200


**ROLLPRO-roller Ø 600 mm**  
*with scrapers  
without comb harrow*

E 1280 570	600
E 1280 571	700
E 1280 572	800
E 1280 573	900
E 1280 574	1.000
E 1280 575	1.200


**FARMFLEX-roller Ø 586 mm**  
*with scrapers  
without comb harrow*

E 1280 580	600
E 1280 581	700
E 1280 582	800
E 1280 583	900
E 1280 584	1.000
E 1280 585	1.200



QUIV OGNE