

HYDRUN

Air / Dirt / Magnetite Separator

HY-S-ADM

Full Stream



→ 1-3 days delivery

→ 1-3 hours start-up

Protect the system's sensitive components

The Hydrun Separator Air/Dirt/Magnetite (HY-S-ADM) combines air venting and particle separation in a single unit. It effectively removes air, dirt, and magnetite to protect the system's sensitive components. Its service-friendly design makes it easy to flush and clean, ensuring stable operation.

Powerful separation

Powerful magnetic bars are used to prevent magnetite from passing through.

Cost-Effective Protection

Protects pumps, valves, and heat exchangers from dirt and magnetite.

Energy Saving

Save energy by continuously reducing the amount of dirt and magnetite in the system.

Easy to install

Compact and easy to install.

penable filter housing

Facilitates cleaning and servicing.

Easy and quick cleaning

The separator and magnet can be cleaned without being removed from the system.

Model name	HY-S-ADM-50	HY-S-ADM-65	HY-S-ADM-80	HY-S-ADM-100	HY-S-ADM-125	HY-S-ADM-150
Previous name	Air, Dirt, and Magnetite Separator DN50	Air, Dirt, and Magnetite Separator DN65	Air, Dirt, and Magnetite Separator DN80	Air, Dirt, and Magnetite Separator DN100	Air, Dirt, and Magnetite Separator DN125	Air, Dirt, and Magnetite Separator DN150
Previous item no.	HL1131	HL1132	HL1133	HL1134	HL1135	HL1136
Connection	Flanged DN50	Flanged DN65	Flanged DN80	Flanged DN100	Flanged DN125	Flanged DN10
Gauss	11,000	11,000	11,000	11,000	11,000	11,000
Maximum temperature	110°C	110°C	110°C	110°C	110°C	110°C
Maximum operating pressure	10 bar	10 bar	10 bar	10 bar	10 bar	10 bar
Maximum flow rate	9 m³/h	14 m³/h	21 m³/h	35 m³/h	54 m³/h	83 m³/h
Weight	22 kg	24 kg	34 kg	38 kg	75 kg	89 kg

hydrun.se/en/product/separator-air-dirt-magnetite • +46 573 21 630 • support@hydrun.se • sales@hydrun.se