

HYDRUN

Filter Housing, cartridge, 3x10" HY-FHC-3-10



→ 1-3 days delivery

→ 1-3 hours commissioning

Standalone filter unit

The Hydrun Filter House Cartridge 3x10" (HY-FHC-3-10) is a stand-alone filter unit that separates both particles and magnetite in hydronic . It helps keep the system fluid clean, reduce clogging, and protect sensitive components for smoother operation.

Powerful separation

Powerful magnetic bars are used to prevent magnetite from passing through.

Flexible filtration level

The filter cartridge is available in several different micron ratings; adjust the filtration level as needed.

Energy Saving

Save energy by continuously reducing the amount of dirt and magnetite in the system.

penable filter housing

Facilitates cleaning and servicing.

Easy and quick cleaning

The separator and magnet can be cleaned without being removed from the system.

Model name	HY-FHC-3-10
Previous name	MA-X 310
Previous item no.	HL3310
Filtration	Cartridges (3)
Filter rating	5, 25, or 50 microns
Gauss	7,000 (x3)
Maximum filter housing temperature	110°C
Maximum cartridge temperature	80°C
Maximum operating pressure	10 bar
Maximum pressure drop	1.5 bar
Maximum flow rate	65 l/min
Media	Water, ethylene, propylene, glycol

hydrun.se/en/product/filter-house-cartridge-3x10 • +46 573 21 630 • support@hydrun.se • sales@hydrun.se