



Swd Rheinol Favorit FAV

SAE 5W-30

Fully synthetic low HTHSV Heavy duty diesel engine oil

Description and Properties

Swd Rheinol Favorit FAV 5W-30 features "Low-SAPs", high performing and efficient additive technology that is designed to deliver enhanced fuel economy and lower emissions.

Protection is enhanced with synthetic technology that significantly reduces engine friction and delivers extended maintenance intervals.

Swd Rheinol Favorit FAV 5W-30 is suitable for the very latest engine technologies

Because of the reduced HTHS Viscosity it offers enhanced fuel Economy capability.

The low-ash formulation helps control blocking or poisoning of exhaust after-treatment devices.

It is helping maintain emission compliance and engine fuel efficiency

Swd Rheinol Favorit FAV 5W-30 is suited for the latest EURO 6 engine technologies requiring a FA-4 quality diesel oil.

It is not backward compatible and cannot be used in older engines.

Specifications / Recommendations

ACEA F01

API FA-4 / SN / SN Plus

Cummins CES 20087

DDC 93K223

DTFR 15C130 (MB 228.61)

Ford M2C214-B1

JASO DH-2

MACK EOS-5

Renault RLD-5

Volvo VDS-5

Typical Properties

Swd Rheinol Favorit FAV SAE 5W-30	unit	value	method
Density at 15°C	kg/m ³	855	DIN 51 757
Viscosity at 40°C	mm ² /s	73,8	DIN 51 562
Viscosity at 100°C	mm ² /s	9,8	DIN 51 562
Viscosity Index		164	DIN ISO 2909
CCS at -30°C	mPa.s	6220	DIN 51 377
Pourpoint	°C	-39	DIN ISO 3016
Flashpoint	°C	228	DIN ISO 2592
TBN	mg KOH/g	10,6	DIN ISO 3771

Article-No. : 31313

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further information to be available by MSDS.

The product has to be labelled according to CLP regulation

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 31919-0
Fax: 0203 / 3191999