



# Swd Rheinol Fouke 4T

## SAE 10W60

### High Performance Multigrade Oil for Motorcycles

#### Description and Properties

**Swd Rheinol Fouke 4T 10W60** is a high performance special engine oil for all motor cycles with air- and water-cooled 4-stroke engines of highest output.

It is the ideal partner for all sportive motor-cycles, on all roads and off-road.

The high capacity is assured by a combination of high quality base oils with successfully tested additives.

**Swd Rheinol Fouke 4T 10W60** offers

- optimal lubrication in motor and in gear and assured functionality of wet clutches even at extreme operation conditions and continuous use.
- outstanding motor cleanliness, especially at pistons and valves.
- an extreme viscosity range and a high viscosity index.

#### Specifications / Recommendations

ACEA A3  
API SP  
JASO MA2

#### Typical Properties

Swd Rheinol Fouke 4T SAE 10W60	unit	value	method
Density at 15°C	kg/m <sup>3</sup>	853	DIN 51 757
Viscosity at 40°C	mm <sup>2</sup> /s	155	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	23,3	DIN 51 562
Viscosity Index		181	DIN ISO 2909
Dynam. Viscos.at -25°C	mPa.s	6470	DIN 51 377
Pourpoint	°C	-45	DIN ISO 3016
Flash point	°C	232	DIN ISO 2592
TBN	mg KOH/g	6,8	DIN ISO 3771

**Article-Number :** 32360

Specification variations in these characteristics may occur.  
The instructions of manufacturer must be regarded.  
Further information to be available by MSDS.

**Swd Lubricants GmbH & Co. KG**  
Am Schlütershof 26  
D-47059 Duisburg  
Tel.: 0203 / 31919-0  
Fax: 0203 / 3191998