



Swd Rheinol Primus FOS Plus

SAE 0W-30

Special high-performance engine oil for Ford Engines

Description and Properties

Swd Rheinol Primus FOS Plus SAE 0W-30 is a special high-performance engine oil based on synthesis technology. It has been developed specifically for use in Ford engines. This special additive - technology ensures an excellent lubrication safety.

Through the combined effect of low viscosity with the specially developed additives high fuel saving is made possible and thus the reduction of CO₂ - emissions. Modern engines make caused by downsizing and modern start-stop systems more and greater demands on the engine oil. These are guaranteed with superior wear characteristics and additional power reserves by the new technology.

The used additive - package has been specially developed for the high demands of the new Ford WSS M2C-950-A.

Specifications / Recommendations

- ACEA C2
- Ford WSS M2C-950-A
- STJLR.03.5007
- Fiat 9.55535-DS1/-GS1
- VW VWC 53035

Typical Values

Swd Rheinol Primus FOS Plus SAE 0W-30	unit	value	method
Density at 15°C	kg/m ³	844	DIN 51 757
Viscosity at 40°C	mm ² /s	54,2	DIN 51 562
Viscosity at 100°C	mm ² /s	10,1	DIN 51 562
Viscosity Index		175	DIN ISO 2909
CCS at -35°C	mPa.s	5620	DIN 51 377
Pourpoint	°C	-45	DIN ISO 3016
Flashpoint	°C	230	DIN ISO 2592

Article-No. : 31194

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further information to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Phone: 0203 / 31919-0
Fax: 0203 / 3191998