



Swd Rheinol Hydralube ZHF-2

Synthetic power steering and central hydraulic fluid

Product description

Swd Rheinol Hydralube ZHF-2 is especially suitable as a synthetic hydraulic agent in very different hydraulic systems, such as power steering systems, levelling systems, hydraulic pneumatic spring systems, shock absorbing devices, hydrostatic driving gears, ABS/ASR and ASC systems, hydraulically controlled couplings, and electro-hydraulic folding roof control systems, etc.

Swd Rheinol Hydralube ZHF-2 is based on premium and modern base oils together with special additives in order to obtain the following unique properties:

- Extremely positive viscosity development due to an exceptional high viscosity index > 300 (!)
- Very low pour point
- Very strong anti-foaming properties
- Good compatibility with seals
- Green coloured

Specification / Recommendation

| | | |
|-----------------------|------------------------------|-----------------------------|
| Bentley JNV862564F | MAN M 3289 | Vauxhall 93160548 |
| BMW 81 22 9 407 758 | MB 345.0 | Volvo 1161 259 / 3074 1424 |
| BMW 82 11 1 468 041 | Opel B 040 0070 / B 040 2012 | VW/Audi G 002 000 |
| BMW 83 29 0 429 576 | Pentosin CHF-202 | (TL 52 146) |
| Chrysler MS-11655B | Porsche 000 043 203 33 | VW/Audi G 004 000 |
| Fendt X 902 011 622 | Porsche 000 043 206 56 | (TL 52 146.01, TL 52 519-B) |
| FORD M2C-204-A / -A2 | Porsche 000 043 206 74 | VW/Audi G 004 012 |
| GM B 040 2012 | PSA S71 2710 | ZF TE-ML 02K |
| Hyundai 00232-19017 | SAAB 3032 380 / 9316 0548 | |
| Land Rover LR 003 401 | | |

Typical Properties

| Swd Rheinol Hydralube ZHF-2 | unit | value | method |
|-----------------------------|--------------------|-------|-----------------|
| Density at 15°C | kg/m ³ | 849 | DIN 51 757 |
| Colour | | green | visual |
| Viscosity at 100°C | mm ² /s | 6,0 | DIN EN ISO 3104 |
| Viscosity at 40°C | mm ² /s | 18,7 | DIN EN ISO 3104 |
| Viscosity index | | 310 | DIN ISO 2909 |
| Flashpoint | °C | 140 | DIN ISO 2592 |
| Pourpoint | °C | < -51 | ISO 3016 |

Article-No. : 30027

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further information to be available by MSDS

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 3191940
Fax: 0203 / 3191998