



Swd Rheinol ATF ULV

Ultra Low Viscosity (ULV) Automatic Transmission Fluid

Description

Swd Rheinol ATF ULV – is an Ultra Low Viscosity automatic transmission fluid based on a outstanding combination of high-quality hydrocrack oils with a special additive technology.

Application

Swd Rheinol ATF ULV was developed for use in 6, 8 and 10 automatic transmissions.

Properties

Swd Rheinol ATF ULV affords following benefits:

- Exceptional oxidation behavior
- Low viscosity for high fuel economy
- smoother shifts over a long period of time
- excellent anti-rust properties
- low foaming tendency

Specification / Recommendation

Aisin Warner AW-2
BMW 83 22 2 413 477 (ATF 7)
Ford WSS-M2C949-A
Ford Mercon ULV
Ford P/N XT-12-ULV [ULV]
Ford Motorcraft XT-12-QULV
GM Dexron ULV
GM 19352619
Mazda ATF A7
MB 236.16 & 236.17
Nissan Matic P, P/N 999MP-MTP10P
PSA 16 350 560 80
Volvo P/N 31 492 172, 31492 173
VW G 053 001 A2
VW G 060 540 A2

Typical Values

Swd Rheinol ATF ULV	unit	value	method
Density at 15	kg/m ³	846	DIN 51 757
Viscosity at 100°C	mm ² /s	4,9	DIN 51 562
Pourpoint	°C	-45	DIN ISO 3016
Flash Point	°C	212	DIN ISO 2592

Warensorten-Nummer : 31635

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further information to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 3191940
Fax: 0203 / 3466540