



Swd Rheinol Favorit FAM

SAE 0W-20

Engine oil for commercial vehicle diesel engines

Description and Properties

Swd Rheinol Favorit FAM 0W-20 is a fuel-efficient engine oil specially developed for modern commercial vehicle engines with advanced exhaust aftertreatment systems.

Swd Rheinol Favorit FAM 0W-20 is characterized by very good cold start properties and low oil consumption

Due to its lower HTHS viscosity (High Temperature High Shear), our product offers improved fuel efficiency and thus reduces fuel costs.

The advanced low-ash formulation helps prevent the contamination and degradation of exhaust aftertreatment systems. Its state-of-the-art additive technology ensures minimal wear and deposit formation, delivering outstanding piston cleanliness and contributing to extended engine life.

Specifications / Recommendations

DTFR15C140 (MB 228.71)

Typical Properties

Swd Rheinol Favorit FAM SAE 0W-20	unit	value	method
Density at 15°C	kg/m ³	848	DIN 51 757
Viscosity at 40°C	mm ² /s	38,5	DIN 51 562
Viscosity at 100°C	mm ² /s	7,4	DIN 51 562
Viscosity Index		163	DIN ISO 2909
CCS at -35°C	mPa.s	5600	DIN 51 377
Pourpoint	°C	-45	DIN ISO 3016
Flashpoint	°C	224	DIN ISO 2592
TBN	mg KOH/g	9,1	DIN ISO 3771
Article-No. :		31317	

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further information to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 31919-0
Fax: 0203 / 3191999