



Swd Rheinol Fouke 4T

SAE 10W50

High Performance, Semi-Synthetic Multigrade Oil for Motorcycles

Description and Properties

Swd Rheinol Fouke 4T 10W50 is a high performance special, semi-synthetic engine oil for motor cycles with air- and water-cooled 4-stroke engines of highest output. It is the ideal partner for all sportive motor-cycles, on all roads and off-road.

The high capacity is assured by a combination of high quality base oils with successfully tested additives.

Swd Rheinol Fouke 4T 10W50 offers

- optimal lubrication in motor and in gear and assured functionality of wet clutches even at extreme operation conditions and continuous use.
- outstanding motor cleanliness, especially at pistons and valves.
- highest wear protection of all power transmission components in motor and gear.
- good cold-starting and low friction properties.
- all-seasons use at temperate climate.

Specifications / Recommendations

ACEA A3
API SP
JASO MA2

Typical Properties

Swd Rheinol Fouke 4T SAE 10W50	unit	value	method
Density at 15°C	kg/m³	853	DIN 51 757
Viscosity at 40°C	mm²/s	110	DIN 51 562
Viscosity at 100°C	mm²/s	17,2	DIN 51 562
Viscosity Index		171	DIN ISO 2909
Dynam. Viscos.at -25°C	mPa.s	4980	DIN 51 377
Pourpoint	°C	-39	DIN ISO 3016
Flash point	°C	228	DIN ISO 2592
TBN	mg KOH/g	6,8	DIN ISO 3771

Article-Number : 32350

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further information to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 31919-0
Fax: 0203 / 3191998