



Swd Rheinol Primus ASM

SAE 0W-8

Premium low-friction engine oil

Discription and Properties

Swd Rheinol Primus ASM SAE 0W-8 is a premium low-friction engine oil that provides excellent wear protection, reduces oil and fuel consumption, keeps the engine clean, and ensures rapid lubrication.

Swd Rheinol Primus ASM SAE 0W-8 offers:

- High shear stability and optimal aging stability
- Fast lubrication even at low temperatures
- Excellent wear protection
- Reduced pollutant emissions and fuel economy

Specifications / Recommendations

API SQ (RC)
JASO GLV-1

Typical Properties

Swd Rheinol Primus ASM SAE 0W-8	unit	value	method
Density at 15°C	kg/m ³	845	DIN 51 757
Viscosity at 40°C	mm ² /s	25	DIN 51 562
Viscosity at 100°C	mm ² /s	5,2	DIN 51 562
Viscosity Index		140	DIN ISO 2909
CCS at -30°C	mPa.s	6190	DIN 51 377
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	230	DIN ISO 2592
TBN	mg KOH/g	7,2	DIN ISO 3771
Article-No. :		31175	

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further information to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Phone: 0203 / 31919-0
Fax: 0203 / 3191999