



# Swd Rheinol ATF DX VI - LV

## AUTOMATIC TRANSMISSION FLUID

### Description

**Swd Rheinol ATF DX VI - LV** – fluid is a fully synthetic, low viscosity Automatic Transmission Fluid which is made with a special additive technology, optimized for a wide range of passenger car applications.

### Application

**Swd Rheinol ATF DX VI - LV** is used in an extensive range of European, American and Asian passenger car service fill applications. Additional it can be used in commercial vehicle applications and power steering, too.

### Properties

**Swd Rheinol ATF DX VI - LV** affords following benefits:

- Exceptional oxidation behavior
- Low viscosity for high fuel economy
- smoother shifts over a long period of time
- excellent anti-rust properties
- low foaming tendency

### Specification / Recommendation

DEXRON VI	Honda/Acura DW-1, ATF Type 3.0
Aisin Warner AW-1	Honda 082000-9017 (ATF Type 3.1)
Aisin Warner AW F8FXX	Hyundai/Kia NWS-9638 T-5
Aisin Warner JWS 3324, ATF-0WS	Hyundai/Kia WS, spec NWS-9638
ATF 134 / 3353 / L12108 / M-1375.4	Hyundai/Kia P/N 040000C90SG
ATF M-1375.6 / Shell 3403-M115	Hyundai/Kia SP4-M1 / SP-IV / SP-IV-RR
Bentley P/N PY112995PA	Hyundai/Kia SPH-IV
BMW ATF 3+, ATF 6	Isuzu SCS
BMW M-L12108	Jaguar 02JDE 26444 / Fluid 8432
BMW/Mini P/N 83 22 0 142 516	JASO M315, Class 1A-LV
BMW/Mini P/N 83 22 0 397 114	Jeep ATF LGF8
BMW/Mini P/N 83 22 2 163 514 (BMW 8072 B)	Land Rover P/N TYK500050
BMW/Mini P/N 83 22 2 152 426	Land Rover LR0022460-AW-1
BMW/Mini P/N 83 22 2 289 720	Land Rover P/N LR0022460: LV
BMW/Mini P/N 83 22 2 305 396 (ATF 2)	Land Rover LR023288/023289
BMW/Mini P/N 83 22 2 305 397	Maserati P/N 231603
BMW/Mini P/N 83 22 2 355 599	Mazda FW 6A EL, FW 6AX EL
BMW/Mini P/N 83 22 2 355 601	Mazda FZ
Chrysler/Dodge/Jeep P/N 05127382AA	Mercon LV
Chrysler/Dodge/Jeep P/N 68043742AA	Mitsubishi ATF-J3
Daimler / Mercedes MB 236.12, 236.14, 236.41	Mitsubishi SP-IV
FIAT 9.55550-AV1	Mitsubishi Dia Queen ATF-MA1
Fiat Chrysler 8&9 Speed ATF	Mitsubishi Dia Queen ATF-PA
Fiat Chrysler AW-1	Nissan/Infinity Matic-S / Matic-W
Fiat Chrysler Dex-VI	Porsche P/N 000 043 304 00
Fiat Chrysler P/N 05127382	Saab P/N 93 165 147 - AW-1
Fiat Chrysler P/N 68157995AA/AB	Shell 3353, Shell 134, Shell 1375.4
Fiat Chrysler SP-4, P/N 68171866AA	Subaru WS
Fiat Chrysler SP-IV, P/N 68171866AA	Suzuki Matic S
Fiat Chrysler SP-IV, P/N 68171869AA	Toyota/Lexus/Scion WS
FORD/Lincoln/Mercury Spec Ford WSS-M2C938-A/SF,	Volvo P/N 31 256 774, 31 256 775
P/N XT-10-QLV [LV]	VW/Audi G 052 533, G 055 005 (-A, A2)
FORD/Lincoln/Mercury P/N XT-6-QSP or -DSP [SP]	VW/Audi G 055 540 (A2)
FORD/Lincoln/Mercury Spec WSS-M2C922-A1	VW/Audi G 055 162 A2 or A6
GM Dex HP	VW/Audi G 060 162 A2
GM/GMC/Opel/Saturn AW1	ZF Lifeguard 6 / 8 / 9
GM/GMC/Opel/Saturn P/N 88863400	
GM/GMC/Opel/Saturn P/N 88863401	



# Swd Rheinol ATF DX VI - LV

## AUTOMATIC TRANSMISSION FLUID

### Typical Values

Swd Rheinol ATF DX VI - LV	unit	value	method
Density at 15	kg/m <sup>3</sup>	849	DIN 51 757
Farbe		red	Visual
Viscosity at 40°C	mm <sup>2</sup> /s	28,1	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	5,7	DIN 51 562
Viscosity Index		150	DIN ISO 2909
Pourpoint	°C	-45	DIN ISO 3016
Flash Point	°C	212	DIN ISO 2592

**Warensorten-Nummer : 32847**

Specification variations in these characteristics may occur.  
The instructions of manufacturer must be regarded.  
Further information to be available by MSDS.

**Swd Lubricants GmbH & Co. KG**  
Am Schlütershof 26  
D-47059 Duisburg  
Tel.: 0203 / 3191940  
Fax: 0203 / 3466540