



Please ask Swd Lubricants GmbH & Co.KG before the export to China, because the product has to be registered.

Swd Rheinol Hydralube ZHF

High performance hydraulic fluid for automotive aggregates

Product description

Swd Rheinol Hydralube ZHF is a synthetic hydraulic fluid which meets the highest requirements for modern automotive aggregates. It can be used for subsequent units:

Power steering, level control, shock absorber, hydropneumatic suspension, stability- and traction-systems, electrohydraulic convertible steering mechanism and central locking.

Swd Rheinol Hydralube ZHF has been developed for the use of life-use. It has a range use from -40°C to over 130°C at full performance.

Swd Rheinol Hydralube ZHF is recommended for following automobile manufacturers: BMW, Ford, Daimler, GM / Opel, MAN, Porsche, Saab and Volvo.

Specification / Recommendations

Audi G004000, P/N G002000, P/N G002012
 Chrysler MS-1872, MS-5931, MS-9602, MS-11655
 Ford M2C195-A
 GM 88901975, 89021184, 89021187, 9985010, 9985835
 Hyundai PSF-3, PSF-4, 00232-19017
 MB 236.3, 345.0
 MAN 3289
 Mitsubishi PS Fluid & Diamond SP III
 Nissan PSF-II
 Saab 93160548, 30 09 800, 30 32 380
 Subaru K0209A0080
 Toyota Type EH 008886-01
 VW TL 521 146, P/N G002000, P/N G002012
 Volvo 30741424, P/N 1161529

Typical Properties

Swd Rheinol Hydralube ZHF	unit	value	method
Density at 15°C	kg/m ³	859	DIN 51 757
Colour		green	visual
Viscosity at 100°C	mm ² /s	24,7	DIN EN ISO 3104
Viscosity at 40°C	mm ² /s	6,8	DIN EN ISO 3104
Viscosity index		262	DIN ISO 2909
Flashpoint	°C	152	DIN ISO 2592
Pourpoint	°C	-51	ISO 3016

Article-No. : 30019

Specification variations in these characteristics may occur.
 The instructions of manufacturer must be regarded.
 Further information to be available by MSDS

Swd Lubricants GmbH & Co. KG
 Am Schlütershof 26
 D-47059 Duisburg
 Tel.: 0203 / 3191940
 Fax: 0203 / 3191998