



Swd Rheinol Fouke 4T

SAE 10W40

High Performance, Semi-Synthetic Multigrade Oil for Motorcycles

Description and Properties

Swd Rheinol Fouke 4T SAE 10W40 is a high performance special, semi-synthetic engine oil for motor cycles with air- and water-cooled 4-stroke engines of highest output.

It is the ideal partner for all sportive motor-cycles, on all roads and off-road.

The high capacity is assured by a combination of high quality base oils with successfully tested additives.

Swd Rheinol Fouke 4T SAE 10W40 offers

- optimal lubrication in motor and in gear and assured functionality of wet clutches. even at extreme operation conditions and continuous use.
- outstanding motor cleanliness, especially at pistons and valves.
- good cold-starting properties.

Specifications / Recommendations

ACEA A3
API SP
JASO MA2

Typical Properties

Swd Rheinol Fouke 4T SAE 10W40	unit	value	method
Density at 15°C	kg/m³	852	DIN 51 757
Viscosity at 40°C	mm²/s	88,2	DIN 51 562
Viscosity at 100°C	mm²/s	14,4	DIN 51 562
Viscosity Index		170	DIN ISO 2909
Dynam. Viscos.at -25°C	mPa.s	5290	DIN 51 377
Pourpoint	°C	-39	DIN ISO 3016
Flash point	°C	230	DIN ISO 2592
TBN	mg KOH/g	7,0	DIN ISO 3771

Article-Number : 32340

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further information to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 31919-0
Fax: 0203 / 3191998