Swd Rheinol Primol Power Synth CS SAE 5W-40

High Performance Low Friction Motor Oil for Passenger Cars

Description and Properties

Swd Rheinol Primol Power Synth CS SAE 5W-40 is a low friction oil to be used in passenger cars gasoline and diesel engines. It is produced by blending high quality hydrocrack-components (HC) from the synthesis technology and highly-developed additives.
Suitable also under severe operating conditions in modern passenger car engines, turbo- or non-turbo charged.

Swd Rheinol Primol Power Synth CS SAE 5W-40 by its optimized formulation provides lowered fuel- and oil consumption. Because of its outstanding viscosity-/temperature behaviour it provides a multigrade characteristic, which allows the all-seasons use in areas of strong daily or seasonal thermal fluctuations.
The dispersing power, expressed by the performance level of this product, prevents deposits and pluggings in the oil circuit and thus keeps the engine clean.
Modern oxidation inhibitors extend the service life of the oil and the optimal wear protection cares for long engine life.

Specifications / Recommendations

ACEA A3 / B4
API SQ
MB 229.1
PSA B71 2294
Renault RN0700 / RN0710
VW 501.01 / 505.00

Typical Properties

Swd Rheinol Primol Power Synth CS SAE 5W-40	unit	value	method
Density at 15°C	kg/m³	852	DIN 51 757
Viscosity at 40°C	mm²/s	82,6	DIN 51 562
Viscosity at 100°C	mm²/s	13,5	DIN 51 562
Viscosity Index		167	DIN ISO 2909
CCS at -30°C	mPa.s	5950	DIN 51 377
HTHS-Viscosity at 150°C	mPa.s	min. 3,5	ASTM D5481
Pourpoint	°C	-39	DIN ISO 3016
Flashpoint	°C	226	DIN IS0 2592
TBN	mg KOH/g	10,9	DIN ISO 3771
Article-Number :		**31244**	

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further information to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 31919-0
Fax: 0203 / 3191999