Swd Rheinol Fouke 4T
SAE 5W40 FHC

Fully Synthetic High Performance Multigrade Oil for Motorcycles

Description and Properties

Swd Rheinol Fouke 4T 5W40 FHC is a high performance, fully synthetic special engine oil for motor cycles with air- and water-cooled 4-stroke engines of highest output.
It is the ideal partner for all sportive motor-cycles, on all roads and off-road.
The high capacity is assured by a combination of high quality base oils with successfully tested additives.

Swd Rheinol Fouke 4T 5W40 FHC offers

- optimal lubrication in motor and in gear and assured functionality of wet clutches. even at extreme operation conditions and continuous use.
- outstanding motor cleanliness, especially at pistons and valves.
- good cold-starting properties.

Specifications / Recommendations

API SP
JASO MA2

Typical Properties

Swd Rheinol Fouke 4T SAE 5W40 FHC	unit	value	method
Density at 15°C	kg/m³	847	DIN 51 757
Viscosity at 40°C	mm²/s	87,6	DIN 51 562
Viscosity at 100°C	mm²/s	14,4	DIN 51 562
Viscosity Index		171	DIN ISO 2909
Dynam. Viscos.at -30°C	mPa.s	6130	DIN 51 377
Pourpoint	°C	-42	DIN ISO 3016
Flash point	°C	224	DIN IS0 2592
TBN	mg KOH/g	6,5	DIN ISO 3771

Article-Number :	**32313**

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further information to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 31919-0
Fax: 0203 / 3191998