Swd Rheinol Primus LLD
SAE 0W-20

High Performance Fuel Economy Oil for Passenger Cars

Description and Properties

Swd Rheinol Primus LLD SAE 0W-20 is a high-alloyed, all-seasons oil for those passenger car engines, which require fuel economy (FE) oils. Low viscosity of special base oils coming from the synthesis-technology provides by fast oil circulation and low frictional resistance noticeable reduction of fuel consumption and pollutant emission.

Swd Rheinol Primus LLD SAE 0W-20 is equal to all thermal and mechanical loads, which may occur in modern fuel economy passenger car engines.

- high cleaning-and dit holding capacity (Detergent/Dispersant) provide excellent motor cleanliness.
- outstanding fuel economy properties by special friction reducing additives.
- cost-effective all-seasons oil with noticeable fuel reduction.
- takes care for the enviroment by reduced emissions of CO_2 and particles.

Specifications / Recommendations

ACEA C5, C6
API SP
MB 229.71
Ford WSS-M2C952-A1
GM dexos D
Haval (GWM)
MG (SAIC)
Opel OV0401547-A20
Jaguar / Land Rover STJLR.03.5006
Li-auto

Typical Values

Swd Rheinol Primus LLD	unit	value	method
Density at 15°C	kg/m³	846	DIN 51 757
Viscosity at 40°C	mm²/s	41,7	DIN 51 562
Viscosity at 100°C	mm²/s	8,3	DIN 51 562
Viscosity Index		176	DIN ISO 2909
CCS at -35°C	mPa.s	5820	DIN 51 377
Pourpoint	°C	-45	DIN ISO 3016
Flashpoint	°C	228	DIN IS0 2592
TBN	mg KOH/g	7,4	DIN ISO 3771
Article-No. :		**31150**	

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further information to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Phone: 0203 / 31919-0
Fax: 0203 / 3191999