

NT60E

Rock Picker

MODEL	NT60E
Width (Picking)	1,52 m
Transport Width (with tires) machine centered with tractor	2,97 m
Working Width: To center of tractor (machine is offset to right of tractor)	4,18 m
Transport Length	6,22 m
Operating Length	6,10 m
Height	1,86 m
Dumping Height	2,13 m
Weight	3722.9 kg
Tongue Weight	513 kg
Bucket Capacity	1,97 m ²
Tire Size	400/60-22,5
Tire Pressure	4,275 Bar (427,5 kPa)
Required Horsepower	70 PS (52 kw)
Recommended Horsepower	135 PS (101 kw)
Hydraulic Hitch	Yes
Hydraulic Drive	Yes

MODEL	NT60E
Picking Style	Reel
Number of Batts	3
Minimum Rock Diameter	50 mm
Maximum Rock Diameter	610 mm
Lift Cylinder	89 mm x 864 mm
Recommended	@3 km/h – 23 rpm @6 km/h – 47 rpm
Hydraulic Outlets Required	3
Hydraulic Pressure	172,36 Bar (17236 kPa)
Flow Requirement	68 l/min
Frame	152 mm x 102 mm x 6 mm (H x B x T) Rectangular Tubing
Replaceable Tines	Main Apron Tines are replaceable to allow for high acre usage
Hard Surfacing	Reel Arm Teeth and Apron Tines (Standard)
Hopper Bottom is Grated	Yes
Hopper Back is Grated	Yes
Brakes	Hydraulic

While every effort has been made to ensure that the information is accurate/current at the time of production, all specifications are subject to change.

For the latest product information, please visit: www.highlinemfg.com.