



Rental services for specialized foundation engineering with fixed-price expertise. www.borama.rent



BG 30 H Low Headroom System – BT 75

DRILLING RIGS

Technical data

BG 30 H Low Headroom System – BT 75**DRILLING RIGS**


Kelly Drilling

CFA
Continuous
Flight Auger DrillingFDP
Full Displacement PilingFoW
Front of Wall

Bio-oil



Low Headroom

**BG 30 H Low Headroom System – BT 75**

Technical data	
Rotary drive	KDK 300 S
Torque for casing operation	300 kNm
Max. speed of rotation	53 rpm
Drill axis	1,100 mm
Crowd winch	
Max. sledge stroke	3,960 (4,420)* mm
Crowd force push and pull	423 kN
Speed (down/up)	9.9 m/min
Fast speed (down/up)	32 m/min

* Sledge stroke with original masthead

Main winch	
Line pull	270 kN
Line speed (max.)	85 m/min
Auxiliary winch	
Line pull	100 kN
Line speed (max.)	55 m/min
Base carrier BT 75	
Engine	CAT C 9.3 B
Rated output	310 kW / 1,850 rpm
Exhaust emission	EU Stage V / Tier 4 final
Hydraulic pressure	350 bar
Flow rates	2x250 + 1x400 + 1x135 l/min
Under carriage UW 110	
Transport width	3,000 mm

Complete
data sheet


< 2 of 2 >

BG 30 H Low Headroom System – BT 75

DRILLING RIGS



Transport position




Complete data sheet



BG 30 H Low Headroom System – BT 75

Transport weights	
Machine without counterweight	60.3 t
Counterweights (1x 4.9 t + 2x 2.5 t)	9.9 t
KDK 300 S	5.5 t
Kelly bars BK 280/419/5/19 – K 280/419/5/28 – BK 280/419/5/33	4.2 – 5.2 – 5.8 t

Rental services for specialized
foundation engineering
with fixed-price expertise.



BORAMA Rent GmbH
Neustädter Straße 27
92685 Floß

+49 9603 903 163-0

info@borama.rent
www.borama.rent

Efficient, close by.

-  Headquarters
-  Service locations