


14 HP | 32 CFM Engine-Driven Pressure Lubricated Reciprocating Compressor


32 CFM @ 175 PSI

Features

- Heavy-duty two-stage pressure lubricated pump
- Disk and spring valves
- Centrifugal unloader
- Bearings on both ends of the crank shaft
- Needle bearings and inserts on rods
- Torrington needle bearings
- Swedish steel valves
- Access to compressor valves without compressor head removal
- Industrial-duty engine
- Alternator on drive engine
- ASME/CRN certified air receiver
- Critical controls protected by compressor base plate
- Drive engine on left side for safety
- Fully enclosed belt guard
- Full saddle mounting feet instead of pegged mounting feet
- Heavy-duty air filter
- Pilot valve continuous operation
- Stainless steel flexible air lines
- 2-groove B width drive pulley
- 2-piece tank/top plate design



Air cooled after cooler on Platinum models



Platinum Features

- All basic features
- Automatic tank drain
- Belt guard after cooler
- On-board battery mounted and wired (no truck wiring needed)
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

Model	HP	CFM @ 100 PSI	CFM @ 175 PSI	Engine Brand	Starter	Tank	LxWxH	Weight
CI14GEK30-CI10PL	14	33	32	Kohler	Electric	30 Gallon Horizontal	49x22x42	700

Add -P after model number to make Platinum Model. Available in basemount configuration without tank.

No Start Up Kit Required

Lifetime Parts Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 04-2026



Scan to visit our website

