

7.5 HP | 40.6 CFM Duplex Reciprocating Compressors

Features

- Heavy-duty two-stage solid cast iron pumps
- Disk and spring valves
- Centrifugal unloaders
- Bearings on both ends of the crank shaft
- Needle bearings and inserts on rods
- Torrington needle bearings
- Swedish steel valves
- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME/CRN certified air receiver
- Auto start/stop
- Fully enclosed belt guards
- Heavy-duty air filters
- Industrial grade electric motors
- TEFC drive motors (3 phase only)
- Magnetic starter mounted and wired
- Stainless steel flexible air lines
- 2-groove B width motor pulley
- 2-piece tank top plate design

Platinum Features

- All basic features
- Automatic tank drain
- Belt guard mounted after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

Time Delay
40.6 CFM @
175 PSI

Alternating
20 CFM @
175 PSI



Air cooled after cooler on Platinum models



Model	HP	CFM @ 100 PSI	CFM @ 175 PSI	Voltage	Tank	LxWxH
DCI7521E120H	7.5	45	40.6	208-230/1	120 Gallon Horizontal	80x29x55
DCI7523E120H	7.5	45	40.6	208-230/480/3	120 Gallon Horizontal	80x29x55

Add -P after model number to make Platinum Model

No Start Up Kit Required

Lifetime Parts Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 04-2026



Scan to visit our website

