

15 HP | 40.1 CFM Pressure Lubricated Reciprocating Compressor


Features

- Heavy-duty pressure lubricated two-stage solid cast iron pump
- Disk and spring valves
- Centrifugal unloader
- Bearings on both ends of the crank shaft
- Needle bearings, and inserts on rods
- Torrington needle bearings
- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME/CRN certified air receiver
- Auto start/stop
- Fully enclosed belt guard
- Heavy-duty air filter
- Industrial grade electric motor
- TEFC drive motor (3 phase only)
- Magnetic starter mounted and wired
- Stainless steel flexible air lines
- 2-groove B width motor pulley
- 2-piece tank/top plate design

Platinum Features

- All basic features
- Automatic tank drain
- Belt guard mounted after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

40.1 CFM @ 175 PSI



Air cooled after cooler on Platinum models



Model	HP	CFM @ 175 PSI	Voltage	Tank	LxWxH	Weight
CI1523E120H-PL	15	40.1	208-230/480/3	120 Gallon Horizontal	70x26x45	975

Add -P after model number to make Platinum Model.

No Start Up Kit Required

Lifetime Parts Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 04-2026



Scan to visit our website

