

# 7.5 HP | 40.6 CFM Duplex Pressure Lubricated Reciprocating Compressors

## Features


- Heavy-duty pressure lubricated two-stage solid cast iron pumps
- Disk and spring valves
- Centrifugal unloaders
- Bearings on both ends of the crank shafts
- Needle bearings, and inserts on rods
- Torrington needle bearings
- Swedish steel valves
- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME/CRN certified air receiver
- Auto start/stop
- Fully enclosed belt guards
- Heavy-duty air filters
- Industrial grade electric motors
- TEFC drive motors (3 phase only)
- Magnetic starter mounted and wired
- Stainless steel flexible air lines
- 2-groove B width motor pulley
- 2-piece tank/top plate design

## Platinum Features

- All basic features
- Automatic tank drain
- Belt guard mounted after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

Time Delay  
40.6 CFM @  
175 PSI

Alternating  
20 CFM @  
175 PSI



Air cooled after cooler on Platinum models



| Model           | HP  | CFM @ 100 PSI | CFM @ 175 PSI | Voltage       | Tank                  | LxWxH    |
|-----------------|-----|---------------|---------------|---------------|-----------------------|----------|
| DCI7521E120H-PL | 7.5 | 45            | 40.6          | 208-230/1     | 120 Gallon Horizontal | 80x29x55 |
| DCI7523E120H-PL | 7.5 | 45            | 40.6          | 208-230/480/3 | 120 Gallon Horizontal | 80x29x55 |

Add -P after model number to make Platinum Model.

No Start Up Kit Required

Lifetime Parts Warranty Available

## Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 04-2026



Scan to visit our website

