

22.5 HP | 39 CFM Engine-Driven Rotary Screw Compressor

40 CFM @
100 PSI

39 CFM @
150 PSI

Features

- Heavy-duty single stage rotary screw airend
- Industrial-duty drive engine
- Heavy-duty air filter
- Spin on oil filter
- Spin on separator
- ASME/CRN certified air receiver
- Drive engine on left side for easy access and safety
- Easy to read and access gauges
- Easy to remove bolt on oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Fully enclosed belt guard
- Full saddle mounting feet instead of pegged mounting feet
- Operating pressures from 100-190 PSI available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- 220 PSI maximum working pressure

Platinum Features

- All basic features
- Battery mounted and wired
- Tank discharge ball valve
- Vibration isolation pads
- Free freight in the 48 states & southern Canada



Model	HP	CFM @ 100 PSI	CFM @ 150 PSI	Engine Brand	Starter	Tank	LxWxH	Weight
R18GEH33	22.5	40	39	Honda	Electric	30 Gallon	48x30x48	700
R18DEK33	22.5	40	39	Kohler Diesel	Electric	30 Gallon	48x36x48	725

Add -P after model number to make Platinum Model. Available in basemount configuration without tank.

No Start Up Kit Required

Lifetime Parts Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 04-2026



Scan to visit our website

