

10 HP | 36-38 CFM Rotary Screw Compressor


75 dBA

38-40 CFM
@ 125 PSI

36-38 CFM
@ 150 PSI

Features

- Heavy-duty single stage rotary screw airend
- Belt guard mounted air/oil cooler
- Self tensioning electric motor base
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy-duty air filter
- Operating pressures from 100-190 PSI available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Spin on separator
- TEFC drive motor (3 phase only)
- 2-piece tank/top plate design
- UL control components
- 220 PSI maximum working pressure
- Plato Smart Touchscreen controls with real-time monitoring, easy troubleshooting, maintenance reminders, and remote accessibility



Belt guard mounted air/oil cooler



Platinum Features

- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- Tank discharge ball valve
- Freight pre-paid in the 48 states & southern Canada

Model	HP	CFM @ 125 PSI	CFM @ 150 PSI	Voltage	Tank	LxWxH	Weight
R101V83-S	10	38	36	208-230/1	80 Gallon Vertical	45x27x74	750
R103V83-S	10	40	38	208-230/480/3	80 Gallon Vertical	45x27x74	750
R101H83-S	10	38	36	208-230/1	80 Gallon Horizontal	60x24x45	725
R103H83-S	10	40	38	208-230/480/3	80 Gallon Horizontal	60x24x45	725
R103V123-S	10	40	38	208-230/480/3	120 Gallon Vertical	43x30x78	850
R103H123-S	10	40	38	208-230/480/3	120 Gallon Horizontal	72x28x45	850

Add -P after model number to make Platinum Model.

No Start Up Kit Required

Lifetime Parts Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 04-2026



Scan to visit our website

