

Tonnage		2.0 Ton	
iAIR - R32 Cooling Only		ATD-CF24SMR3-A02/SE143	
Power Supply		208-230V/1N/60Hz	
Minimum Circuit Amp.	A	13.5	
Max. Overcurrent Protection	A	20	
Cooling	Capacity	Btu/h	22000
	SEER2 / EER2	Btu/h.W	14.3 / 11.7
Heating	Capacity	Btu/h	/
	HSPF2	Btu/h.W	/
Compressor Type / Brand		Scroll	
Fan Motor	Type	PSC	
	Rated HP	1/9	
Outdoor Coil		Inner Grooved Copper Tube and Hydrophilic Aluminum Fin	
Air Flow	CFM	1600	
Sound Pressure Level	dB(A)	60	
Dimension	Unit (WxHxD)	inch	23-3/5 x 25 x 23-3/5
	Packing(WxHxD)	inch	24-4/5 x 26-1/5 x 24-4/5
Net / Gross weight	lbs	132 / 139	
Refrigerant Connection	Liquid Side	inch	3/8
	Gas Side	inch	3/4
Refrigerant Chargeless	ft[m]	25[7.5]	
Shipping per SDT40HQ		228	



[www.iAIR-USA.com](http://www.iAIR-USA.com)