

Tonnage		4.0 Ton	
iAIR - R32 Cooling Only		ATD-CF48SMR3-C01/SE143	
Power Supply		208-230V/1N/60Hz	
Minimum Circuit Amp.	A	23.4	
Max. Overcurrent Protection	A	40	
Cooling	Capacity	Btu/h	44500
	SEER2 / EER2	Btu/h.W	14.3 / 11.7
Heating	Capacity	Btu/h	/
	HSPF2	Btu/h.W	/
Compressor Type / Brand		Scroll	
Fan Motor	Type	PSC	
	Rated HP	1/3	
Outdoor Coil		Inner Grooved Copper Tube and Hydrophilic Aluminum Fin	
Air Flow	CFM	3200	
Sound Pressure Level	dB(A)	65	
Dimension	Unit (WxHxD)	inch	29-1/7 x 32-7/8 x 29-1/7
	Packing(WxHxD)	inch	30-1/2 x 34-1/20 x 30-1/2
Net / Gross weight	lbs	204 / 214	
Refrigerant Connection	Liquid Side	inch	3/8
	Gas Side	inch	7/8
Refrigerant Chargeless	ft[m]	25[7.5]	
Shipping per SDT40HQ		135	



[www.iAIR-USA.com](http://www.iAIR-USA.com)