

TAG:



**3 Ton Split System
Heat Pump - 1 Phase
DHP5036E1000***

Standard Features:

- Eco-friendly R32 refrigerant with low GWP value
- Energy-efficient scroll compressor
- Equipped with thermal overload protection
- High quality condenser with inner-groove copper tube and aluminum fin
- Service valves with sweat connections and easy-access gauge ports
- Factory-installed high-pressure switch
- AHRI certified and ETL listed

Cabinet Features:

- Compact design allows for easy of installation, clearance, serviceability
- Powder-painted galvanized steel cabinet
- Protective steel louvered coil guard Steel wire axial fan guard
- Unique Fan blade for quieter operation



Model	W - inch [mm]	H - inch [mm]	L - inch [mm]	GAS VALVE SIZE in.	LIQUID VALVE SIZE in.
DHP5036E1000*	29-1/7 [740]	25 [635]	29-1/7 [740]	3/4	3/8

PRODUCT SPECIFICATIONS

NOMINAL CAPACITY	3 Ton
Cooling (BTU/h)	32,400
Heating (BTU/h)	33,000
ELECTRICAL DATA	
Voltage / Phase (60 Hz)	208/230/1
Min. / Max. Voltage	187/253
MCA	19.5
MOP	30
COMPRESSOR	
Type	Scroll
Stage	Single
RLA	13.5
LRA	86
Crankcase Heater	YES
CONDENSER COIL	
Type	Tube & Fin
FAN MOTOR	
Motor Type	PSC
Capacitor(uF)	6
Horsepower (HP)	1/7
Full Load Amps (FLA)	1
REFRIGERATION SYSTEM	
Liquid Line Size ("O.D.)	3/8"
Suction Line Size ("O.D.)	3/4"
Refrigerant Chargeless (ft.)[m]	25 [7.5]
OPERATION RANGE	
Cooling(°F)	55-120
Heating(°F)	5-90
SHIPPING DIMMENTION - (IN.) [mm]	
Width	30-1/2[775]
Height	26-1/8[665]
Length	30-1/2[775]
SHIPPING WEIGHT	
Shipping (LBS.) [kg]	181 [82.1]



Note: Product specifications change from time to time as product improvements and developments are released and may vary from those in this document.