

| | | | |
|------------------------------|----------------|--|---------------------------|
| Tonnage | | 4.0 Ton | |
| iAIR - R32 Cooling & Heating | | ATD-HF48SMR3-C01/SE143 | |
| Power Supply | | 208-230V/1N/60Hz | |
| Minimum Circuit Amp. | A | 28.3 | |
| Max. Overcurrent Protection | A | 45 | |
| Cooling | Capacity | Btu/h | 44000 |
| | SEER2 / EER2 | Btu/h.W | 14.3 / 11.7 |
| Heating | Capacity | Btu/h | 43000 |
| | HSPF2 | Btu/h.W | 7.5 |
| Compressor Type / Brand | | Scroll | |
| Fan Motor | Type | PSC | |
| | Rated HP | 1/3 | |
| Outdoor Coil | | Inner Grooved Copper Tube and Hydrophilic Aluminum Fin | |
| Air Flow | CFM | 3200 | |
| Sound Pressure Level | dB(A) | 65 | |
| Dimension | Unit (WxHxD) | inch | 29-1/7 x 32-7/8 x 29-1/7 |
| | Packing(WxHxD) | inch | 30-1/2 x 34-1/20 x 30-1/2 |
| Net / Gross weight | lbs | 221 / 231 | |
| Refrigerant Connection | Liquid side | inch | 3/8 |
| | Gas side | inch | 7/8 |
| Refrigerant Chargeless | ft[m] | 25[7.5] | |
| Shipping per SDT40HQ | | 135 | |



www.iAIR-USA.com