

Tonnage		3.5 Ton	
iAIR - R32 Cooling & Heating		ATD-HF42SMR3-C01/SE143	
Power Supply		208-230V/1N/60Hz	
Minimum Circuit Amp.		A	23
Max. Overcurrent Protection		A	40
Cooling	Capacity	Btu/h	38000
	SEER2 / EER2	Btu/h.W	14.3 / 11.7
Heating	Capacity	Btu/h	39000
	HSPF2	Btu/h.W	7.5
Compressor Type / Brand		Scroll	
Fan Motor	Type	PSC	
	Rated HP	1/7	
Outdoor Coil		Inner Grooved Copper Tube and Hydrophilic Aluminum Fin	
Air Flow		CFM	2600
Sound Pressure Level		dB(A)	65
Dimension	Unit (WxHxD)	inch	29-1/7 x 32-7/8 x 29-1/7
	Packing(WxHxD)	inch	30-1/2 x 34-1/20 x 30-1/2
Net / Gross weight		lbs	202 / 212
Refrigerant Connection	Liquid side	inch	3/8
	Gas side	inch	3/4
Refrigerant Chargeless		ft[m]	25[7.5]
Shipping per SDT40HQ		135	



[www.iAIR-USA.com](http://www.iAIR-USA.com)