



# ASGARD LINE

Midweight Remote-Controlled Weapon Station

**C-UAS ready**

# TECHNICAL SPECIFICATIONS

## STANDARD CONFIGURATION

Dimensions	
Height	520 mm
Width	1700 mm
Length	1850 mm
Swing radius	1278 -2180 mm
Weight	840 - 950 kg

Performance	
Elevation range	+80° / -10°
Azimuth range	n × 360°
Aiming accuracy	<0,7mrad
Angular speed	120°/s

## MODULAR CONFIGURATION OPTIONS

Modularity	Asgard 230	Asgard 134	Asgard 503
Main gun	30 x 113 mm 265 rounds	7.62 x 51 mm 5000 rounds	12.7 x 99 mm 1200 rounds
Coax	7.62 x 51 mm 2000 rounds	No	No
Rockets	LH/RH side mounted	LH/RH side mounted	LH/RH side mounted
Second optics	Yes	Yes	Yes



The configuration shown is provided for illustrative purposes only and may be adapted to customer-specific requirements due to the system's modular design. The scope of supply, appearance, performance data, dimensions and weights are based on information available at the time of printing. We reserve the right to make changes to colour, form and technical specifications without prior notice. Typographical errors and omissions excepted. Any vehicles depicted are the property of their respective owners and are shown solely for visualisation purposes. Their inclusion does not imply endorsement, cooperation or affiliation.

**Valhalla Turrets d.o.o.**  
Pod lipami 2, 1218 Komenda, Slovenia, EU  
info@valhalla-turrets.com  
www.valhalla-turrets.com