MATERIAL SAFETY DATA SHEET

MaxiDry® 56-426



General description

Created in response to demand for an oil-repellent version of MaxiFlex®, MaxiDry® delivers Controlled Performance™ in wet and oily conditions while remaining thin, flexible, dexterous and comfortable.

Engineered for precision handling, it combines LIQUItech® for advanced liquid resistance, GRIPtech® for enhanced control without fatigue, and ERGOtech® for exceptional comfort and fit.

This balance of protection and dexterity makes MaxiDry® ideal for industries where oils, coolants or liquids are present, ensuring dry, confident handling all day long.

MaxiDry® Oil™ - repellence, grip and comfort in perfect balance.

Compliances

ATG®, herby declares, that this PPE Type is in conformity with the relevant Union harmonisation legislation: Regulation (EU) 2016/425 and the relevant harmonized standards No.: EN ISO 21420:2020 - General requirements, EN 388:2016 + A1:2018, EN ISO 374-1:2016 + A1:2018, EN ISO 374-5:2016.

Use

Liquid proof work glove for Controlled Performance™ in oily or wet conditions.

For detailed applications where this product can be used please consult the ATG® website at www.atg-glovesolutions.com.

Main ingredients

Liner: Nylon,Spandex

Hazardous ingredients

REACH

All ingredients used in the manufacturing and construction of this product are compliant with the EU directive for the "Regulation of chemicals and their safe use" more commonly known as REACH -- EU directive EC 1907/2006. REACH stands for "Registration, Evaluation, Authorisation and Restrictions of Chemical substances". The key aim of REACH is to provide high levels of protection to human health and the environment.

More information can be found at: https://single-market-economy.ec.europa.eu/sectors/chemica.

OEKO-TEX®

This product has been tested and successfully passed the OEKO-TEX® STANDARD 100 global standard which indicates that the product is skin friendly. Look for the OEKO-TEX® logo to make sure you are buying a skin safe product.

More information can be found at: www.oeko-tex.com.

Precautions for use

Before usage, inspect the protective product for any defects or imperfections. If it is ripped or punctured during use dispose them immediately. Wear an appropriate size as too loose or too tight fitting products increase the risk for injuries.

Storage requirements

Store in a cool; dry place which is away from direct sunlight and/or heat. Extended exposure to direct sunlight or excessive heat will reduce shelf life and resulting in fading, discoloration and cracking. Normal anticipated shelf life is 5 years.

Disposal

After the product has been used it may be contaminated with infectious or other hazardous materials. Please dispose to local authority regulations.

Fire notes

The product will decompose at high temperatures. Extinguish using water, CO_2 spray our dry powder.

First aid

Remove contaminated PPE (Personal Protective Equipment). Skin contact: if an allergic reaction occurs seek medical advice immediately. Eye contact; rinse thoroughly with low pressure water. If any prolonged discomfort, seek medical advice immediately.

This document is the property of ATG® and the information contained herein is proprietary to ATG Hand Care (Pvt) Ltd.
Spur Road 7, Phase 2 - IPZ, Katunayake - Sri Lanka - T +94-11-48389000 - F +94-11-2253887 - E info@atg-glovesolutions.com.

MATERIAL SAFETY DATA SHEET

MaxiDry® 56-426

Issue date: 16/07/2026