Instructions for Use for 30-202

Use

Mechanical work glove with thermal resistance in cold or warm and dry or wet environments.

Can be used for temperatures down to -10°C at high activity. Lower activity limits the thermal properties.

Performance values are indicated in the table.

Typelist and performance values

	EN ISO 21420:2020+A1:2024
	EN 388:2016 + A1:2018: **1241B**
	EN 511:2006: **X1X**
	EN 407:2020: **X2XXXX**

Performance values relate to the palm area of the glove.

Certified sizes

6 (XS) - 11 (2XL)

Declarations

CE

Category II
Medium risk

EU Declaration of conformity

ATG®, hereby declares, that this PPE Type is in conformity with the relevant Union harmonisation legislation: Regulation (EU) 2016/425 and the relevant harmonized standards (EN).

Download (/download/22dafc98-7329-4277-8dce-1be783e16874)

UKCA

Category II
Medium risk

UKCA Declaration of conformity

ATG®, hereby declares, that this PPE Type is in conformity with the Personal Protective Equipment Regulations (Regulation 2016/425 and the Personal Protective Equipment (Enforcement) Regulations 2018: Great Britain).

Download (/download/00d72415-79af-4658-8a16-4e57fff26d0e)

Warnings

Does not protect against chemicals.

The product is liquid repellent but not liquid proof.

Does not protect against puncture through sharp objects such as needles or swarf.

This product is tear resistant and cannot be worn when using rotating machines or when there is a risk of entanglement in machine parts.

This glove may cause a restriction in movement of your hands.

Before use, inspect the product for any defects or imperfections and avoid wearing a damaged, heavily soiled, worn or dirty (also internally) product of any substance, this could irritate and/or infect the skin and cause dermatitis. In this event, seek medical advice from the company doctor or consult a dermatologist.

Donning

Wash and dry your hands completely before donning the gloves.
Ensure the product fits well.

Doffing

When removing your gloves, place the fingertips into the palm of the other glove.
Pull the glove until almost off. Repeat on the other hand. With both gloves almost off shake both hands to remove the gloves fully.

Care instructions

Storage / Cleaning

Store the product in it's original packaging in a cool and dry place.
Keep away from direct sunlight, heat, flame and sources of O...

Keep away from direct sunlight, heat, flame and sources of Ozone.

After use, clean the product thoroughly with a dry cloth to remove any contaminants.

If the product has to be re-worn, store it in such a way that the inside lining of the support can dry out easily.

After washing, the fit may differ from that of a new product. However, the gloves will not become shorter than their technical specifications.

The product can be laundered at 40°C/104°F with a standard detergent (3 washing cycles), natural drying.

The product lifetime in use is based on wear and abrasion.

This product can be used until the expiry date displayed on the product stamp.

Disposal / Waste

Used products maybe contaminated with infectious or hazardous substances.

Dispose of according to the Local Authority/Municipality Regulations, landfill or incinerate under controlled conditions.

Explanation of the pictograms

	**EN 388:2016 + A1:2018** Mechanical Hazards • **A: Abrasion resistance** - number of rubs (Level 0-4) • **B: Blade cut resistance** - Coupe Test - Index (Level 0-5) • **C: Tear resistance** - N (Level 0-4) • **D: Puncture resistance** - N (Level 0-4) • **E: TDM Cut resistance** according to ISO 13997 - N (Level A-F)* • **F: Impact protection** according to EN 13594:2015 - Y/N (P=Yes) ** coupe test results are only indicative while the TDM cut resistance test (ISO13997) is the reference performance result.*
	**EN 407:2020** Thermal Hazards (Heat/Fire) • A: Flammability (0-4) • B: Contact heat (0-4) • C: Convective heat (0-4) • D: Radiant heat (0-4) • E: Small splashes of molten metal (0-4) • F: Large quantities of molten metal (0-4) *Performance level 0 indicates that the product fails below the minimum performance level for the given individual hazard.*
	**EN 511:2006** Cold Hazards • A: Convective cold (0-4)

	• A: Convective cold (0-4) • B: Contact cold (0-4) • C: Water impermeability (0-1)

Higher values stand for better protection/resistance.
If "X" is marked as a performance level the test is either not applicable or not proceeded.
Puncture resistance should not be confused with piercing exerted by thin tips or needles.

HandCare®

- Skin Health Alliance Dermatologically Accredited
- REACH compliant
- Sanitized®
- OEKO-TEX® STANDARD 100
- Washable (40°C/104°F)

Constituents / Allergies

Some products may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions.

Skin contact: if an allergenic reaction occurs seek medical advice immediately. Eye contact: rinse thoroughly with

For more information on product selection, usage, performances or potential allergic substances, please contact ATG® or your local distributor.



Latex
The product contains natural rubber latex (NRL), which may cause allergic reactions.

Warranty / limitation of damages

ATG® warrants that this product shall be in accordance with ATG® standard specifications as of the date of delivery to authorized distributors.

Except to the extent prohibited by law, this warranty is in line with all warranties, including any warranty of fitness for a particular purpose; ATG® liability shall be limited to the purchase price of the product at issue.

Buyers and users of this product are deemed to have accepted the terms of this limitation of warranty, which may not be varied by any verbal or written agreement.