TECHNICAL SPECIFICATION

EVO® ALTA™ Baseworker™

White / ARA170-000-100



DESCRIPTION

The new EVO® ALTA™ range offers all-round impact protection. The mountaineering-style helmet features a specialised shell structure and internal liner to increase durability and shock absorption performance. Precise adjustment settings enable a secure fit, ensuring the helmet remains stable.
Engineered to maximise compatibility and accessory integration, the EVO® ALTA™ range is an adaptive system with built-in attachment points, and an interchangeable front module, and a selection of 4-point chinstraps for use in a wide range of applications.

EVO® ALTA™ Baseworker™ non vented meets the mandatory shock absorption and penetration resistance requirements of EN 12492 and is fully EN 397 compliant including an EN 397 compliant chinstrap. The 4-point chinstrap is designed to release under force if caught or snagged. EVO®ALTA™ Baseworker™ non vented meets the electrical insulation requirements of EN 397 and EN 50365:2002

OPTIONS

Black (ARA170-001-100)
Blue (ARA170-000-500)
Extra Visibility Orange (ARA170-001-600)
Extra Visibility Yellow (ARA170-00C-700)
Green (ARA170-000-300)
Red (ARA170-000-600)
White (ARA170-000-100)

SAFETY STANDARDS

EN 397 • EN 50365

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

- Peak: Micro
- Side Impact Resistance: 25 Joules
- Lateral Deformation: Yes
- EN 397 ELECTRICAL INSULATION: 440V (Non-vented only)
- Minimum Temperature: -40°C
- EPP Liner: Yes
- Textile: Harness
- Depth Adjustment: 3D Harness
- Fitted 4 point chinstrap (EN397 Compliant): Fitted
- Reflective Option: Optional
- JSPCheck: Yes
- Size: 53-64cm
- Impact Resistance: 100 Joules
- Molten Metal: Yes
- EN 50365 ELECTRICAL INSULATION: 1000V
- Maximum Temperature: +50°C
- ABS Shell: Yes
- Recyclable: Shell
- Ventilation: No
- Wheel Ratchet: Yes
- Universal Accessories Slot: Yes
- ID card holder: Optional
- Product Weight: 500g

FEATURES



All-Round Protection

EVO® ALTA™ provides all-round impact protection with top, side, front and rear shock absorption performance. The helmet is designed with an extended nape section to offer greater neck coverage.



Compatibility & Accessories

The EVO® Alta™ range maximises compatibility and accessory integration. Attachment points on the front, sides and rear of the helmet shell enable firm fitting of ear defenders, faceshields, goggle and lamp straps, plus a range of other accessories.



Maximum Comfort

The Revolution® Flex wheel ratchet harness secures the helmet, eliminating pressure points to provide maximum comfort. Fitted with a replaceable Chamlon™ cotton sweatband and fully compatible with EVO® cooling sweatbands



Interchangeable Front Module

EVO® ALTA™ features a unique interchangeable front module. Select the integrated ID card holder for on-site identification or choose the logo-ready standard front to apply company branding. Both front modules enable attachment of a helmet lamp and other accessories.



EPP Liner

EVO® ALTA™ features an internal impact liner to increase shock absorption and penetration protection. Manufactured in expanded polypropylene (EPP), the liner is lightweight and ventilated for comfort.



Secure Fit

The harness cradles the head to keep the helmet stable with an adjustable 4-point chinstrap for increased security. 3D-Adjustment depth settings enable the most precise fit attainable on a safety helmet.

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

for protection against heat stress.



4-Point Chinstrap

The 4-point chinstrap is easy to adjust on the head. Size and anchorage point adjustment enable a tailored fit for different head sizes, ensuring stability and greater comfort.



Custom Branding

Helmets can be customised to meet a corporate identity. Logo printing is available for the standard front module, helping to increase brand recognition and discourage theft. MOQs apply.

LOGO

- [x] Front
- [x] Sides

RANGE

evolta™

DOWNLOADS

Image Pack (ZIP)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.