

B-LINE hand held plate bevelling and deburring machines

B2 AIR	B3	B10 ELECTRA (without the milling head)	B15 ELECTRA (without the milling head)	B15 AIR (without the milling head) 27220S (4200RPM) 27220 (6000RPM)	B-Dock (without bevelling machine)	Xpipe Beveler (without bevelling machine)	B15 INOX (without the milling head)	B15 INOX set (without the milling head)	B22 ZERO
Art. Nr.	24220	28220 (400V)	25300 (230V)	25250 (230V)	25350	25500	26250 (230V)	26254 (230V)	29220 (230V)
	pneumatic	electric	electric	electric	electric	accessory for B10 Electra / B15 Electra / B15 AIR	electric	electric	electric
	2 mm / 0.08"	3 mm / 0.12"	10 mm / 0.4"	15 mm / 0.6"	15 mm / 0.6"	5 mm / 0.2"	15 mm / 0.6"	15 mm / 0.6"	20 mm / 0.8"
	45°	30° - 60°	30°, 37.5°, 45°, 50°, 60°	30°, 37.5°, 45°, 50°, 60°	30°, 37.5°, 45°, 50°, 60°	30°, 37.5°, 45°, 60°	30°, 37.5°, 45°, 50°, 60°	30°, 45°, 60°	0° - 60° (Facing!)
	R 1.5 mm / 0.05"	-	R 2.5 mm / 0.10" R 3.5 mm / 0.14" R 4 mm / 0.16"	R 2.5 mm / 0.10" R 3.5 mm / 0.14" R 4 mm / 0.16"	R 2.5 mm / 0.10" R 3.5 mm / 0.14" R 4 mm / 0.16"	R 2.5 mm / 0.10" R 3.5 mm / 0.14" R 4 mm / 0.16"	R 2.5 mm / 0.10" R 3.5 mm / 0.14" R 4 mm / 0.16"	R 2.5 mm / 0.10" R 3.5 mm / 0.14" R 4 mm / 0.16"	-
	400 g / 0.88 lb	31 kg / 68 lb	6 kg / 13.2 lb	9.5 kg / 20.9 lb	7.5 kg / 16.5 lb	28 kg / 62 lb	8.4 kg / 18.5 lb	10.5 kg / 23.1 lb	18.75 kg / 41.33 lb

UZ-LINE plate bevelling machines with automatic feeding


UZ12 ULTRALIGHT Single and Double Bevel	UZ15 RAPID Single and Double Bevel	UZ18 HARDWORKER Single and Double Bevel	3D manipulator Accessory for Bevelers UZ12 Ultralight, UZ15 Rapid, UZ18 Hardworker	UZ29 SPEEDER Single and Double Bevel	UZ30 EXPRESS Single and Double Bevel	UZ47 SKILLMASTER Single and Double Bevel, J-Bevel, Facing, Cladding Removal, Angle over 70°	UZ50 TRIUMPH Single and Double Bevel	UZ100 BOLD Single and Double Bevel, J-Bevel, Facing, Cladding Removal, Angle over 70°	
Art. Nr.	1918 (400V)	1931 (400V)	1980 (400V)	1930	1962 (400V)	25999 (400V)	4700 (400V)	1940 (400V)	1000 (400V)
	electric	electric	electric	accessory for UZ12, UZ15, UZ18	electric	electric	electric	electric	electric
	12 mm / 0.5"	15 mm / 0.6"	18 mm / 0.7"	-	29 mm / 1.14"	30 mm / 1.18"	47 mm / 1.87"	62 mm / 2.44"	100 mm / 3.93"
	22.5°, 30°, 37.5°, 45°, 50°	15° - 50°	15° - 50°	-	22.5°, 30°, 37.5°, 45°, 50°	30° - 60°	0° - 90°	15° - 60°	0° - 90°
	1.8 m/min. / 5.9 ft/min.	3.5 m/min. / 11.48 ft/min.	1.9 m/min. / 6.23 ft/min.	-	1.8 m/min. / 5.9 ft/min.	0.6 - 3.5 m/min. / 1.96 - 11.5 ft/min.	0 - 1.4 m/min. / 0 - 4.59 ft/min.	0 - 1.2 m/min. / 0 - 3.93 ft/min.	0 - 1 m/min. / 0 - 3.28 ft/min.
	30 kg / 66 lb	94 kg / 207 lb	110 kg / 242.5 lb	85 kg / 187 lb	285 kg / 628 lb	400 kg / 881.8 lb	245 kg / 540 lb	250 kg / 551 lb	459 kg / 1012 lb

G-LINE Belt grinders

PASOVEC 100	PASOVEC 100 (incl. STAND)	PASOVEC 75 / 1	PASOVEC 75 / 2	PASOVEC 150 / 1	PASOVEC 150 / 2	PASOVEC 100 MULTI	PASOVEC 75 RUNNER	
Art. Nr.	1100.230 (230V)	1100.230S (230V)	3075-1-3 (400V)	3075-2-3 (400V)	3150-1-3 (400V)	3150-2-3 (400V)	1200 (400V)	1300 (400V)
	100 x 1220 mm / 19m/s	100 x 1220 mm / 19m/s	75 x 2000 mm / 29m/s	75 x 2000 mm / 15m/s, 29m/s	150 x 2000 mm / 29m/s	150 x 2000 mm / 15m/s, 29m/s	100 x 2000 mm / 15m/s, 30m/s	75 x 2000 mm / 29m/s
	1,5 kW	1,5 kW	3 kW	3 kW	4 kW	4 kW	3 kW	3 kW
	38 kg / 83.7 lb	45 kg / 99.2 lb	72 kg / 158.7 lb	72 kg / 158.7 lb	90 kg / 198.4 lb	90 kg / 198.4 lb	159 kg / 350.5 lb	70 kg / 154.3 lb



HIGH SPEED BEVELLING



www.beveler.eu

N.KO spol. s r.o.
a Member of Richtr Group
Táborská 398/22
293 01 Mladá Boleslav
Czech Republic, European Union

nko@nko.cz
www.beveler.eu
English: +420 326 772 001
Spanish: (+34)900953423
Portuguese: (+351)210202803




PIPE LINE - Inside Clamping bevelling machines

NEW

SEAMLESS
READY
STEEL

self-centering



	TWISTER 2	STINGER 28E	STINGER 76E	STINGER 120E	STINGER 159E	STINGER 240E	STINGER 240EA	STINGER 300E	STINGER 330E	STINGER 330EA	STINGER 426E	STINGER 426EA	STINGER 600E	STINGER 600EA	STINGER 830E	STINGER 830EA
Art. Nr.	30° - 27200 37.5° - 27201 / 45° - 27202	30011 (230V)	30012 (230V)	30013 (230V)	30014 (230V)	30015 (230V)	30016 (230V)	30002 (230V)	30017 (230V)	30018 (230V)	30019 (230V)	30020 (230V)	30021 (230V)	30022 (230V)	30029 (230V)	30030 (230V)
Tool for	B10 / B15 Electra	electric (1200W)	electric (1200W)	electric (1500W)	electric (1500W)	electric (2000W)	electric (2000W)	electric (1800W)	electric (2000W)	electric (2000W)	electric (2400W)	electric (2400W)	electric (2400W)	electric (2400W)	electric (2400W)	electric (2400W)
ID	19.5 mm - OD 70 mm ID 0.76" - OD 2.75"	ID 18 - 28 mm / OD max. 50 mm ID 0.7" - 1.1" / OD max. 1.96"	ID 28 - 76 mm / OD max. 89 mm ID 1.1" - 2.99" / OD max. 3.5"	ID 40 - 120 mm / OD max. 126 mm ID 1.57" - 4.72" / OD max. 4.96"	ID 65 - 159 mm / OD max. 168 mm ID 2.55" - 6.25" / OD max. 6.61"	ID 80 - 240 mm / OD max. 273 mm ID 3.14" - 9.44" / OD max. 10.74"	ID 80 - 240 mm / OD max. 273 mm ID 3.14" - 9.44" / OD max. 10.74"	ID 36 - 269 mm / OD max. 269 mm ID 1.41" - 10.59" / OD max. 10.59"	ID 150 - 330 mm / OD max. 355 mm ID 5.9" - 12.99" / OD max. 13.97"	ID 150 - 330 mm / OD max. 355 mm ID 5.9" - 12.99" / OD max. 13.97"	ID 250 - 426 mm / OD max. 426 mm ID 9.84" - 16.73" / OD max. 16.73"	ID 250 - 426 mm / OD max. 457 mm ID 9.84" - 16.73" / OD max. 17.99"	ID 300 - 600 mm / OD max. 630 mm ID 11.81" - 23.62" / OD max. 24.8"	ID 300 - 600 mm / OD max. 630 mm ID 11.81" - 23.62" / OD max. 24.8"	ID 600 - 830 mm / OD max. 850 mm ID 23.62" - 32.67" / OD max. 33.46"	ID 600 - 830 mm / OD max. 850 mm ID 23.62" - 32.67" / OD max. 33.46"
mm	≤15 mm / 0.59"	≤15 mm / 0.59"	≤15 mm / 0.59"	≤15 mm / 0.59"	≤20 mm / 0.78"	≤20 mm / 0.78"	≤75 mm / 2.95"	≤15 mm / 0.59"	≤20 mm / 0.78"	≤75 mm / 2.95"	≤20 mm / 0.78"	≤75 mm / 2.95"	≤20 mm / 0.78"	≤75 mm / 2.95"	≤20 mm / 0.78"	≤75 mm / 2.95"
kg	450 g / 0.99 lb	10 kg / 22 lb	10 kg / 22 lb	18 kg / 39 lb	25 kg / 55 lb	35 kg / 77 lb	45 kg / 99 lb	36.6 kg / 80.6 lb	52 kg / 114 lb	62 kg / 132 lb	90 kg / 199 lb	107 kg / 236 lb	115 kg / 253 lb	110 kg / 242.5 lb	182 kg / 401 lb	220 kg / 485 lb
QR																

PIPE LINE - Outside Clamping bevelling machines


NEW

SEAMLESS
READY
STEEL

auto-feed



	Xpipe Beveler (without bevelling machine)	C-BITER 63E	C-BITER 76E	C-BITER 89E	C-BITER 114E	PHYTON 63ESC	PHYTON 114ESC	PHYTON 89ES	PHYTON 168ES	PHYTON 230ES	PHYTON 275ES	PHYTON 305ES	PHYTON 325ES	PHYTON 377ES	PHYTON 426ES	PHYTON 457ES
Art. Nr.	25500	30025 (230V)	30026 (230V)	30047 (230V)	30048 (230V)	30027 (230V)	30028 (230V)	30031 (230V)	30023 (230V)	30032 (230V)	30033 (230V)	30024 (230V)	30034 (230V)	30035 (230V)	30036 (230V)	30037 (230V)
Accessory for	B10 / B15 Electra	electric (1300W)	electric (1300W)	electric (1300W)	electric (1300W)	electric (1300W)	electric (1300W)	electric (1500W)	electric (2000W)	electric (2000W)	electric (2000W)	electric (2000W)	electric (2000W)	electric (2000W)	electric (2000W)	electric (2000W)
OD	≥85 mm / 3.36"	OD 32 - 63 mm OD 1.25" - 2.48"	OD 42 - 76 mm OD 1.65" - 2.99"	OD 63 - 89 mm OD 2.67" - 3.50"	OD 76 - 114 mm OD 2.99" - 4.48"	OD 76 - 114 mm OD 2.99" - 4.48"	OD 76 - 114 mm OD 2.99" - 4.48"	OD 25 - 89 mm OD 0.98" - 3.50"	OD 50 - 168 mm OD 1.96" - 6.61"	OD 80 - 230 mm OD 3.14" - 9.05"	OD 125 - 275 mm OD 4.92" - 10.82"	OD 150 - 305 mm OD 5.9" - 12"	OD 168 - 325 mm OD 6.61" - 12.79"	OD 219 - 377 mm OD 8.62" - 14.84"	OD 273 - 426 mm OD 10.74" - 16.77"	OD 300 - 457 mm OD 11.81" - 17.99"
mm	≤15 mm / 0.59"	/	/	/	/	≤12 mm / 0.47"	≤12 mm / 0.47"	≤30 mm / 1.18" (80 mm / 3.14")	≤30 mm / 1.18" (80 mm / 3.14")	≤30 mm / 1.18" (80 mm / 3.14")	≤30 mm / 1.18" (80 mm / 3.14")	≤30 mm / 1.18" (80 mm / 3.14")	≤30 mm / 1.18" (80 mm / 3.14")	≤30 mm / 1.18" (80 mm / 3.14")	≤30 mm / 1.18" (80 mm / 3.14")	≤30 mm / 1.18" (80 mm / 3.14")
kg	8.4 kg / 18.5 lb	9 kg / 19.8 lb	10 kg / 22 lb	14 kg / 30.8 lb	15 kg / 33 lb	13 kg / 28.6 lb	17 kg / 37.4 lb	28 kg / 61.7 lb	50 kg / 110.2 lb	53 kg / 116.8 lb	56 kg / 123.4 lb	63 kg / 138.8 lb	65 kg / 143.3 lb	68 kg / 149.9 lb	75 kg / 165.3 lb	80 kg / 176.3 lb
QR																



	PHYTON 508ES	PHYTON 560ES	PHYTON 610ES	PHYTON 630ES	PHYTON 660ES	PHYTON 715ES	PHYTON 762ES	PHYTON 830ES	PHYTON 914ES
Art. Nr.	30038 (230V)	30039 (230V)	30040 (230V)	30041 (230V)	30042 (230V)	30043 (230V)	30044 (230V)	30045 (230V)	30046 (230V)
electric	(2400W)	electric (2400W)	electric (2400W)	electric (2400W)	electric (2400W)	electric (2400W)	electric (2400W)	electric (2400W)	electric (2400W)
OD	OD 355 - 508 mm OD 13.97" - 20"	OD 400 - 560 mm OD 15.74" - 22.04"	OD 457 - 610 mm OD 17.99" - 24.01"	OD 480 - 630 mm OD 18.89" - 24.80"	OD 508 - 660 mm OD 20" - 25.98"	OD 560 - 715 mm OD 22.04" - 28.14"	OD 600 - 762 mm OD 23.62" - 30"	OD 660 - 813 mm OD 25.98" - 32"	OD 762 - 914 mm OD 30" - 35.98"
mm	≤30 mm / 1.18" (80 mm / 3.14")	≤30 mm / 1.18" (80 mm / 3.14")	≤30 mm / 1.18" (80 mm / 3.14")	≤30 mm / 1.18" (80 mm / 3.14")	≤30 mm / 1.18" (80 mm / 3.14")	≤30 mm / 1.18" (80 mm / 3.14")	≤30 mm / 1.18" (80 mm / 3.14")	≤30 mm / 1.18" (80 mm / 3.14")	≤30 mm / 1.18" (80 mm / 3.14")
kg	102 kg / 224.8 lb	110 kg / 242.5 lb	115 kg / 253.5 lb	120 kg / 264.5 lb	126 kg / 277.7 lb	138 kg / 304.2 lb	150 kg / 330.6 lb	158 kg / 348.3 lb	178 kg / 392.4 lb
QR									

G-LINE Mobile Belt Grinder



Art. Nr.	1300 (400V)	3000 W
	75 mm / 2.95"	70 kg / 154.3 lb
	2000 mm / 78.74"	
	30 m/s / 98.43 ft/s	