

# MCX Tech

## FIELD-IQ

### CROP INPUT CONTROL SYSTEM

Trimble Field-IQ crop input control system is a flow and application control system that prevents seed and fertilizer overlap, controls the rate of material applications, monitors seed delivery and fertilizer blockage, and controls the height of spray booms. The Field-IQ system runs on the TMX-2050™ display, GFX-750™ display and GFX-350™ display. Each of these displays supports a different combination of Field-IQ functionality—giving you the ability to choose the interface option that fits your needs.



### FIELD-IQ FOR PLANTING AND SEEDING

Overlapping inputs will increase your costs and create nutrient deficiency in soil due to overpopulation of seed. The Field-IQ system controls planter clutches and a variety of air seeder systems by automatically turning sections on/off based on non-farm zones and previously planted areas.

Monitoring seed population, eliminating skips and multiples, and maintaining correct seed spacing are critical in producing the maximum yield per acre. The Field-IQ system helps growers prevent yield loss by monitoring the results of singulation analysis in real-time so that adjustments can be made immediately.

Plants can have different nutrient needs throughout the growing season based on soil conditions and other environmental factors.

The Field-IQ system monitors and simultaneously varies the rate of materials to precisely plant seeds, apply chemicals and broadcast fertilizers.

### FIELD-IQ FOR STRAYING

Overlapping spray inputs increase fertilizer and chemical costs while risking potential harm to the environment. The Field-IQ system applies the correct amount of fertilizer and chemicals to your field while preventing spray overlap.

Applying fertilizers and chemicals from the incorrect distance above the crop can increase the risk of damage to crops and the environment. The Field-IQ system automatically adjusts the height of boom sections with sensors that measure the distance between ground cover or plant canopy.

### BENEFITS

#### Field-IQ Systems For Spraying

- Decreases input costs
- Eliminates over-spraying Provides even application of product
- Reduces operator fatigue

#### Field-IQ System For Planting

- Eliminates over-planting
- Increases yield
- Ensures proper seed spacing
- Prevents lodging and nutrient competition
- Creates uniform yield across fields
- Lessens environmental impact

# FIELD-IQ

## CROP INPUT CONTROL SYSTEM



Your Australian AgTech Translators

### Automatic Section Control

- Manage seed, liquid, and anhydrous using inch-level control on up to 48 individual sections
- Overlap detection shows where you've been and what you've done
- Eliminate seed overlap in your headlands and point rows with Tru Count
- Meter Mount™ air clutches
- Eliminate fertilizer overlap with Tru Count LiquiBlock™ valves that easily connect to clutch air lines



### Seed Monitoring

- Advanced seed monitoring increases the quality of seed placement by delivering singulation details from the seeding system to the operator, allowing for on-the-go planter tuning
- Prevent costly planter problems by catching them early before they cause yield reduction
- See results of singulation analysis including information on population, singulation, skips/multiples, spacing, and quality of spacing



### Variable Rate Application Control

- Simultaneously control the application rate of different materials (up to 6 with the TMX-2050 display, 4 with the GFX-750 display, and 2 with the GFX-350 display), including granular seed, granular fertilizer, liquid, and anhydrous ammonia in different combinations
- Variable rate control of materials can be achieved with a prescription VRA map for more efficient fertilizer utilization
- Automate mapping and record keeping as inputs are applied
- Adjust your seed population, fertilizer rates, or spray application manually or using a prescription
- Automatically control spinner speed of spreader application systems to evenly distribute nutrients

Elite Global Full Line PTx Dealer

1300 770 970

**MCX Tech**

