



Datasheet

Specifications CoWin Halo.

Ne verferrunt invel ipisqui atempor arum aut abo. Berioست que imus aut faccati storrov idictus atibus molor sanis volupti volorpo rporpor epudaep udiorehenit mincid que ma voluptatis di sed ernamus enisitia que exped eum sint, nes dolorem poreri comnit alitatio omnis venim derio.

Environmental

Medium Large

IP Rating IPx5	IPx5
Operating temperature 0 - 35 degrees Celsius	0 - 35 degrees Celsius

Processing unit

Medium Large

Processor Intel i3	Intel i3
Operating System Windows 11 IoT Enterprise	Windows 11 IoT Enterprise

Chassis

Medium Large

Dimensions (HxWxD) 825 × 620 × 120 mm	1433 × 879 × 140 mm
Material - Frame 3mm steel, powder coated	3mm steel, powder coated
Material - Touch 10 mm toughened glass	10 mm toughened glass
Weight 45 kg (approximately)	72 kg (approximately)
Strenght norm IEC 62262 - IK10	IEC 62262 - IK10

Display

Medium Large

Screensize 32 inch (81cm)	48 inch (124cm)
Resolution 1920 × 1080 (Full HD)	1920 × 1080 (Full HD)
Orientation Portrait	Portrait

Touch

Medium Large

Technology Projected Capacitive	Projected Capacitive
Touch resolution 2 - 3 mm	2 - 3 mm
Latency < 10 ms	< 10 ms

Audio

Medium Large

Speakers Hidden	Hidden
Range 60 - 20.000 Hz	60 - 20.000 Hz
Output power 2 × 13 Watt	2 × 13 Watt

Power

Medium Large

Rating 100 - 240 Volt (single phase, 50/60 Hz)	100 - 240 Volt (single phase, 50/60 Hz)
Nominal / Maximal 70 Watt / 90 Watt	100 Watt / 140 Watt
Sleep mode 30 Watt	30 Watt



Curious how CoWin works in practice?
Schedule a personal demo.

Want more information?
Visit reconnect.com

**Reconnect brings back
control, calm and clarity.**
Because humanity
should never disappear.



RECONNECT

Human touch.
In every interaction.

Discover more at www.reconnect.nl