

Tandus Imagery

4 Stocked Colours

Medium Scale Pattern

500 x 500mm Tiles

Available with Cushion
Backing

WWW.TARKETT.COM.AU

Tandus

 **Tarkett**

TECHNICAL DATA SHEET

Product Characteristics	Standards	Tandus Imagery ECOPLY PVC Backing	Tandus Imagery Cushion backing
Product Construction		Patterned Loop	Patterned Loop
Yarn Type		100% Solution Dyed Type 6 Nylon	100% Solution Dyed Type 6 Nylon
Gauge		1/10»	1/10»
Primary Backing		Synthetic Non-Woven	Synthetic Non-Woven
Secondary Backing		ECOPLY™ PVC backing	Cushion backing
Stitches/Length	ASTM D-148	42.0/10cm	42.0/10cm
Total Pile Weight		440g/m ²	478g/m ²
Total Weight		4500g/m ²	4300g/m ²
Surface Pile Density	UM44D	177.6kg/m ³	177.6kg/m ³
Thickness of pile above substrate	ASTM D-418	4.0mm (+/- 0.5mm)	4.0mm (+/- 0.5mm)
Total Thickness		6.5mm (+/- 0.5mm)	9.0mm (+/- 0.5mm)
Dimension		500mm x 500mm	500mm x 500mm
Installation Method		Monolithic, Horizontal Ashlar, Quarter Turn, Non-Directional	Monolithic, Horizontal Ashlar, Quarter Turn, Non-Directional
Tiles per box/area		16/4m ²	16/4m ²
Soil/Stain Resistance		Ensure	Ensure
Warranty		15 years	15 years
Performance Characteristics	Standards	Tandus Imagery ECOPLY PVC Backing	Tandus Imagery Cushion backing
Reaction to fire	ISO AS 9239-1	Critical Radiant Flux 6.2kW/m ² Smoke - 247%.min	Critical Radiant Flux 8.3kW/m ² Smoke - 63%.min
Electrostatic Properties	AATCC 134	<3kV	<3kV

Recommended specification clauses for your project:

1. Product must be Tarkett Carpet Tile
2. 100% Solution Dyed Nylon Carpet Tiles 500mm x 500mm with ECOPLY™ and Cushion Backing.
3. 15 years commercial manufacturer's instructions.
4. Must be installed as per manufacturer's instructions.

The information in this datasheet is correct at date of publication however, due to Tarkett's commitment for ongoing product improvement, we reserve the right to change this information without notice. Please note that Tarkett's instructions regarding installation, cleaning and maintenance must be observed. Please contact Tarkett for further information on these instructions.

