

# Standard Plus (1.5 mm)

## Datasheet

Classification	Norm	Tarkett Value
Product type	ISO 10581	Homogeneous vinyl floor covering
winder content	ISO 10581	Type II
Commercial classification	ISO 10874	32 Very Heavy
Industrial classification	ISO 10874	41 Heavy
Technical Characteristics	Norm	Tarkett Value
Surface treatment		PUR
Total thickness	ISO 24346	1.5 mm
Wear layer thickness	ISO 24340	1.5 mm
Total weight	ISO 23997	2400 g/m <sup>2</sup>
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0019-0045-DoP-2013-07
Reaction to fire	AS/ISO 9239.1	Critical radiant flux 11kW/m <sup>2</sup> Smoke 38%.min
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance	EN 12667	~0,010 m <sup>2</sup> ·K/W
Technical Performance	Norm	Tarkett Value
Marine Equipment	IMO 2010 FTP Code part 2 and 5	Approved
Residual indentation	EN ISO 24343-1	Required value: ≤ 0.10 mm Best measured value: 0.04 mm
Slip resistance	AS 4586	P4
Slip resistance	DIN 51130	R10
Curly resultant to heat	EN ISO 23999	≤ 8mm for rolls
Castor chair	ISO 4918	Suitable
Colour fastness to light	ISO 105-B02	≥ 6
Dimensional stability	EN ISO 23999	≤ 0.40 %
Chemical resistance	ISO 26987	Good resistance
Bacteria Resistance	ISO 846 Part C	Does not promote growth
Underfloor heating		Suitable (maximum 27°C)
Wetroom approval	EN 13553 Annex A	Watertight
Seam Strength Average Value	EN 684	≥ 400 N/50mm
Sustainability performances	Norm	Tarkett Value
Vinyl Council Australia		PVC Best Practice
Recyclability through ReStart®		Recyclable
Recycled content		25,5 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		5,71 kg CO <sub>2</sub> e / m <sup>2</sup>
Total VOC Emissions	EN 16516	Platinum (≤ 10 µg/m <sup>3</sup> )
Formaldehyde emission		E1
GreenTag		Level A
Health Rate		Platinum
Dimensions and designs		
Roll	Roll 2 x 23m	
Number of designs available	12	



The above information is subject to modification for the benefit of further improvement (24/11/2025). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.