

EZ CARB ACTIVATED CARBON FILTER



ACTIVE FILTRATION. CONTROL ODORANT VAPOR.

The MRR EZ Carb Activated Carbon Filter draws odorant vapor through a distributed bed of activated carbon in a DOT-approved steel drum. Three active configurations cover 30- and 55-gallon systems, including an extended-suction model for installations where the blower must be separated from the filter drum.

KEY FEATURES

- 30- and 55-gallon active-filter configurations
- Attached-blower and extended-suction arrangements
- DOT-approved 18-gauge steel drums
- Intrinsically safe, hazardous-location-rated motor

APPLICATIONS

Odorant vapor control during normal operation, maintenance, refill, pressure release, equipment failure, and spill response.

MODEL COMPARISON

SPECIFICATION	EZ-030A	EZ-055A	EZ-055A-XS
DRUM VOLUME	30 US gal	55 US gal	55 US gal
DIAMETER	20 in	24 in	24 in drum / 35 in with extension
TOTAL HEIGHT	46 in	50 in	58 in
TOTAL WEIGHT	190 lb	270 lb	330 lb
CARBON WEIGHT	110 lb	180 lb	180 lb
SUCTION HOSE	4.5 in ID x 12 ft	4.5 in ID x 12 ft	4.5 in ID x 18 ft
MOTOR	1/3 hp / 200 CFM	1/3 hp / 200 CFM	1/3 hp / 200 CFM

Motor is specified as intrinsically safe and hazardous-location rated.