

INSTALLATION GUIDE

Your machine.
Ready to brew.

Everything your team needs to get the VendiBean machine installed, connected, and serving specialty coffee — from day one.

110V
STANDARD
POWER

400lb
MACHINE WEIGHT

184°F
BREW TEMP

10K
GALLON FILTER

COMPLIANCE

Internal air gap, check valve, water pump & backflow preventer included. Meets CPC 2022 Section 603.5.12. No external filter or pump required.

POWER REQUIREMENTS

Outlet	Standard 110V
Amperage	15A — no dedicated circuit needed
Daily Usage	4.2 kWh (24-hr operation)
GFCI Outlet	Leviton GFNT2-W (20A / 125V)

MACHINE DIMENSIONS

Height	76.8 in / 6.4 ft
Width	24 in / 2 ft
Depth	26.4 in / 2.2 ft
Weight	400 lbs

Recommended: +6 inches clearance on all sides for ventilation, filter changes, and servicing.

WATER REQUIREMENTS

Line Type	¾-inch braided or PVC line
Temperature	Cold water only
Min Pressure	0.098 MPa
Max Pressure	0.98 MPa
Daily Water	# cups × 10 oz × # days

CUP COMPATIBILITY

Clearance	Up to 6 in. beneath dispenser
Recommended	12 oz — best fit for all recipes
Maximum	16 oz, no taller than 6 inches

FREQUENTLY ASKED QUESTIONS

1. Is a drain required?

No. The machine drains internally into two separate waste buckets — one for liquids, one for coffee grounds. Both are easily emptied as needed.

2. Is an external water filter or pump required?

No. Each machine includes a built-in filtration system with a 10,000-gallon internal water filter.

3. Does the machine need Wi-Fi?

No. The machine connects automatically via cell signal — no Wi-Fi setup required.

4. How do you clean the machine?

Step-by-step cleaning and restocking instructions are available via a video guide. Contact your VendiBean account manager, Stephanie Barber: stephanie.barber@vendibean.com

5. What cups and mugs are compatible?

Up to 6 inches of clearance beneath the dispenser. Recommended: 12 oz. Maximum: 16 oz, no taller than 6 inches.