



Features

- Up to 16ch - Nodestream Live
- Up to 4ch - Nodestream X
- Passively cooled
- Rack and surface mount options
- Built in video wall
- "Passthrough" video output
- 4 x native HDMI input
- Native RS232 serial
- Dual Gigabit LAN
- Analog audio input/output
- Dual redundant wide range DC inputs

Technical Specifications

Channels	Nodestream X	4
	Nodestream Live	16
Physical	Dimensions (H x W x D)	51.5mm x 140mm x 254mm (2.03" x 5.5" x 10")
	Weight	2.2kg (4.85lbs)
Power	Input voltage	12 - 28VDC
	Power consumption	15w (typical)
Environmental	Operating temperature	0 °C to 35 °C / -4 °F to 140 °F
	Humidity	Operating: 0% to 90% (non-condensing)
Certification	RCM, CE, UKCA, FCC	
Video	HDMI output	4 x 1080/60 + 1 x up to 4K/60
	HDMI input	4 x 1080/60p
	USB video source	Uncompressed YUV 4:2:0 / MJPEG
Network Streams	Supported protocols	RTSP/RTP/HTTP/UDP (MPEG,H.264, H.265)
Other Interfaces	USB	2 x Type A 3.0
	Serial	RS232, 3.5mm TRS
	Ethernet	2 x RJ45, 10/100/1000
What's Included	PSU	AC/DC 36w (multi region)
	Serial cable	3.5mm to D9 @1m
	Power cable	4pin DIN to 2.5mm barrel
	Mounts	Surface

