



UZIN MK 250

1-COMPONENT PREMIUM STP WOOD FLOORING ADHESIVE

ENVIRONMENTAL LABELING



EMICODE EC 1 PLUS -
Very low emission



DE-UZ 113 / Environmentally friendly
because of low emissions



French VOC A+ classification

ENVIRONMENTAL PRODUCT DECLARATIONS (EPD)*

- ☐ Product-specific EPD
- ☒ European Model EPD
- ☐ No EPD available



* The detailed life cycle calculation in form of an EPD can be found in a separate document

PRODUCT INFORMATION

Product Carbon Footprint 4,79 kg CO₂e/kg

CO₂ footprint (incl. biogenic C) calculated from cradle to gate
| CO₂ footprint comes from the assigned EPD

GISCODE RS10

Solvent-free flooring materials containing methoxysilane

UZIN MK 250

1-COMPONENT PREMIUM STP WOOD FLOORING ADHESIVE




SUSTAINABLE BUILDING CERTIFICATIONS

If this confirmation is not sufficient, you are welcome to request declarations for your individual building project.



German Sustainable Building Council (DGNB)
DGNB criterion ENV 1.2 Risks for the local environment
Product group 8 Flooring materials
Quality level: QS 4



Quality Seal for Sustainable Buildings (QNG)
Product group 3.1 Flooring materials
Quality level: QNG suitable



Assessment system for sustainable building (BNB)
Product group 10b Flooring materials
Quality level: QS 5



BREEAM: HEA 02 Indoor air quality
Product group "Interior Adhesives and sealants (including flooring adhesives)"
Quality level: BREEAM suitable



LEED requirements in IEQ Credit (4.1)
Low Emitting Materials (LEED v4)
VOC content according to SCAQMD Rule 1168
Quality level: <20 g/L