

FDR16 Series Grooming Mowers

Features	Benefits
3 Cutting widths	48", 60", 72" (102 cm, 152 cm, 183 cm) Able to adapt to various size needs.
Gearbox Horsepower rating	15 - 40 horsepower (11.2 - 22.4 kW) to cover a wide array of tractors.
Rear discharge	The wide, even dispersal of grass leaves a fine thin layer directly behind the mower, vs. a possible windrow to the side. Keeps grass from blowing in unwanted areas. Easier to mow around objects.
Deflectors	Built-in to throw material down, as well as forcing thrown objects down.
Clevis type lower hitch points	Allows for easy connection by being able to remove pins and back into clevises.
Floating 3-point	Top and bottom hitch points float up and down which allows the mower to float over uneven terrain.
Roll formed front on deck.	3/16" (5 mm) roll formed front deck edging for greater strength and impact resistance.
Frame-over-deck design	Frames takes stress out of deck by supporting it.
3/16" (5 mm) Deck thickness	Heavy deck material to aid in overall strength and longevity. Reinforced spindle mounts.
Lower hitch points adjust in and out	Accommodates many tractor configurations by adjusting in and out.
Hard rubber tires	Hard rubber tires are sandwiched between the rim halves, bolted in and can't go flat. Roller bearings allow for a long life.
Heavy-duty Gauge wheel arms	1/4" (8 mm) Gauge wheel arms increases strength.
Non-aligned gauge wheels	Rear wheels don't track behind the front wheels to reduce laying grass over.
High Blade Tip Speed	For cleaner cutting and better dispersion of clippings 48" (102 cm) = 16,203 fpm (82.3 mps) 60" (152 cm) = 18,195 fpm (92.4 mps) 72" (183 cm) = 18,130 fpm (92.1 mps)
Choices of Blades	Low, medium, high-lift, or mulching blades are available to match customer needs and specific applications.
Blade overlap	1 1/4" (32cm) blade overlap assures no skipping in tight turns.
Heavy-duty roller bearings & 1 3/8" machined spindles	Roller bearings for smooth running and quiet operation, 1 3/8" machined spindles for durability, balanced performance, and accuracy. Cast iron housings for added protection and durability.
Top greasing spindles	Assures top bearing gets grease. No shields to remove.
Single B-section Kevlar belt	Simple one belt design. Kevlar material adds additional strength.
Vacuum formed ABS belt guards	No scratching, no rattling.
Spring loaded adjustable idler	Allows for constant and proper tension on belt. Better than adjusting gearbox for belt tension.
Top Hitch	Top hitch has two connection points which allows greater lifting leverage for smaller tractors.
5 Year Limited Gearbox warranty	Shows our confidence in the gearbox integrity. 5 year Parts & Labor with S/N 329841+.
Driveline hanger	For ease of connecting and storing the driveline. Keeps driveline off the ground.
Quick Hitch Compatible	Compatible with Land Pride Quick Hitch for easy attachment and removal increases productivity. [Except 48" (1.22m)]
K-Hitch Interface Option	
Compatible with Land Pride's Model KH15 K-Hitch	Land Pride's KH15 K-Hitch can be used with any Land Pride equipment purchased with the K-Hitch Interface option.
Available on Model FDR1660	Available on our most popular Rear Discharge Grooming Mower Model.
Easy Hook-up	The operator can connect to the K-Hitch Interface from the tractor seat without assisted help when using the KH15 K-Hitch.