



## RTR12 Series

| Features                                                                                | Benefits                                                                                                                                    |
|-----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| American made                                                                           | American made means better quality and parts availability. Most tillers are imported.                                                       |
| Tractor horsepower range<br>1242 & 1250<br>1258 & 1266<br>1274<br>1282                  | 15-40 hp (11-30 kW)<br>20-50 hp (15-38 kW)<br>25-60 hp (19-48 kW)<br>30-60 hp (22-48 kW)                                                    |
| Reverse tilling action                                                                  | Reverse action 'sucks' tiller into ground, does not walk on top of hard ground like forward rotation tillers can.                           |
| 3 Year gearbox warranty                                                                 | Three years on housing, seals, and bearings. Shows our confidence in the product.                                                           |
| 10 Year limited warranty on sprockets and roller chain                                  | Shows our confidence in this product providing many years of service.                                                                       |
| 6 1/2" (17 cm) Digging depth                                                            | For deep soil penetration.                                                                                                                  |
| Parking stand                                                                           | Allows for easy connecting and storage.                                                                                                     |
| Adjustable skid shoes                                                                   | Control depth with seven adjustments.                                                                                                       |
| Formed and reinforced rear tailgate                                                     | Keeps dirt in and leaves a level finish. Forming gives tailgate additional strength. Adjustable tailgate allows for various finish results. |
| Front deflector                                                                         | Front deflector is flexible to take the beating from rocks or debris.                                                                       |
| Bolt in rotor                                                                           | Rotor removes and replaces easier for servicing.                                                                                            |
| 15" (38 cm) Rotor swing diameter                                                        | For deep tilling and turns the soil over faster.                                                                                            |
| 4 "C" shaped heat-treated tines per flange                                              | "C" Shaped tines require less horsepower to move through the ground. Four tines requires less horsepower than 6 tines.                      |
| Double lip seal on rotor bearing                                                        | Double lip seal helps keep the dirt out and the grease in.                                                                                  |
| #80 Drive chain enclosed in oil bath                                                    | Heavy drive chain stretches less, and oil bath keeps wear to a minimum.                                                                     |
| Stamped chaincase cover                                                                 | Stamped forming gives the chain cover strength.                                                                                             |
| <b>3-Point Hitch Option</b>                                                             |                                                                                                                                             |
| Working widths<br>42", 50", 58", 66", 74", & 82"<br>(107, 127, 147, 168, 188, & 208 cm) | A wide range of widths are available to meet specific customer needs.                                                                       |
| Bent plate steel upper hitch                                                            | Plate steel is stronger than flat bar type hitch.                                                                                           |
| Clevis lower hitch                                                                      | Provides additional strength and easy one person connection.                                                                                |
| Offset Capabilities                                                                     | Allows tiller to work closer to objects such as fence lines, buildings and trees. Not available with Land Pride's Quick Hitch.              |
| Fits Land Pride's Quick Hitch                                                           | Allows for quick and easy one person connection. (Offset cannot be used with the Quick Hitch.)                                              |
| Fully shielded slip-clutch driveline                                                    | Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.                             |
| Optional BX driveline                                                                   | This driveline will fit BX Kubota tractors without cutting it to fit.                                                                       |
| <b>K-Hitch Interface Option</b>                                                         |                                                                                                                                             |
| Compatible with Land Pride's K-Hitch                                                    | Land Pride's K-Hitch can be used with any Land Pride equipment purchased with the K-Hitch Interface option.                                 |
| Working widths<br>58" (147 cm) & 66"(168 cm)                                            | Available on our two most popular RTR12 Series models (RTR1258 & RTR1266).                                                                  |
| Easy Hook-up                                                                            | The operator can connect to the K-Hitch Interface with a K-Hitch from the tractor seat without assisted help.                               |
| Fully shielded slip-clutch                                                              | Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.                             |

## RTA12 Series

| Features                                                                                       | Benefits                                                                                                               |
|------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>American made</b>                                                                           | American made means better quality and parts availability. Most tillers are imported.                                  |
| <b>Tractor horsepower range</b><br>1242 & 1250<br>1258 & 1266<br>1274<br>1282                  | 15-40 hp (11-30 kW)<br>20-50 hp (15-38 kW)<br>25-60 hp (19-48 kW)<br>30-60 hp (22-48 kW)                               |
| <b>3 Year gearbox warranty</b>                                                                 | Three years on housings, seals, bearings. Shows our confidence in the product.                                         |
| <b>10 Year limited warranty on sprockets and roller chain</b>                                  | Shows our confidence in this product providing many years of service.                                                  |
| <b>6 1/2" (16.5 cm) Digging depth</b>                                                          | For deep soil penetration.                                                                                             |
| <b>Parking stand</b>                                                                           | Allows for easy connecting and storage.                                                                                |
| <b>Adjustable skid shoes</b>                                                                   | Control depth with various settings.                                                                                   |
| <b>Formed and reinforced rear tailgate</b>                                                     | Forming gives tailgate additional strength. Adjustable tailgate allows for various finish results.                     |
| <b>Bolt in rotor</b>                                                                           | Rotor removes and replaces easier for servicing.                                                                       |
| <b>15" (38 cm) Rotor swing diameter</b>                                                        | For deep tilling and turning the soil over faster.                                                                     |
| <b>4 'C' Shaped heat-treated tines per flange</b>                                              | "C" Shaped tines require less horsepower to move through the ground. Four tines requires less horsepower than 6 tines. |
| <b>Double lip seal on rotor bearing</b>                                                        | Double lip seal helps keep the dirt out and the grease in.                                                             |
| <b>#80 Drive chain enclosed in oil bath</b>                                                    | Heavy drive chain stretches less, and oil bath keeps wear to a minimum.                                                |
| <b>Stamped chaincase cover</b>                                                                 | Stamped forming gives the chain cover strength.                                                                        |
| <b>3-Point Hitch Option</b>                                                                    |                                                                                                                        |
| <b>Working widths</b><br>42", 50", 58", 66", 74", & 82"<br>(107, 127, 147, 168, 188, & 208 cm) | A wide range of widths are available to meet specific customer needs.                                                  |
| <b>Formed plate steel upper hitch</b>                                                          | Plate steel is stronger than flat bar type hitch.                                                                      |
| <b>Clevis lower hitch</b>                                                                      | Provides additional strength and easy one person connection.                                                           |
| <b>Offset Capabilities</b>                                                                     | Allows tiller to work closer to objects such as fence lines, buildings and trees.                                      |
| <b>Fits Land Pride's Quick Hitch</b>                                                           | Allows for quick and easy one person connection. Does not offset to the left with Quick Hitch.                         |
| <b>Fully shielded slip-clutch driveline</b>                                                    | Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.        |
| <b>Optional BX driveline</b>                                                                   | This driveline will fit BX Kubota tractors without cutting it to fit.                                                  |
| <b>K-Hitch Interface Option</b>                                                                |                                                                                                                        |
| <b>Compatible with Land Pride's K-Hitch</b>                                                    | Land Pride's K-Hitch can be used with any Land Pride equipment purchased with the K-Hitch Interface option.            |
| <b>Working widths</b><br>58" (147 cm) & 66"(168 cm)                                            | Available on our two most popular RTA12 Series models (RTA1258 & RTA1266).                                             |
| <b>Easy Connection</b>                                                                         | The operator can connect to the K-Hitch Interface with a K-Hitch from the tractor seat without assisted help.          |
| <b>Fully shielded slip-clutch</b>                                                              | Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.        |