



RTA2570 & RTA3576 Tiller Models

Features	Benefits
American made	Many tillers are imported. American made means better parts availability.
Tractor horsepower range	(RTA2570 Model = 25 - 75 hp) and (RTA3576 Model = 35 - 95 hp)
Gearbox warranty	3 Years on housing, gears, shafts, seals, bearings. Shows our confidence in the product.
Working widths	(RTA2570 Model = 62" & 70" [1.57 & 1.78 m]) And (RTA3576 Model = 76" 1.93 m]) To meet specific customer needs
8" (20 cm) Digging depth	For extra deep soil penetration and cultivation.
Stamped upper hitch plate	Stamped plate adds additional strength to hitch.
Hitch bolted to inside of support	Force is applied downward on top hitch, by bolting hitch to inside of support. Keeps hitch from 'spreading' outward.
Clevis style lower hitch	Allows easier hook-up of lower 3-point arms.
Hitch offset capability	Offset 5" (13 cm) by moving lower hitch points to cover right tire track.
Fits Land Pride Quick Hitch	Allows for quick and easy one person hook-up. Offset can not be used with Quick Hitch.
Adjustable park stand	Allows for easy hook-up and storage.
Adjustable skid shoes	Control depth with various settings.
Wear shield or left skid shoe	Shield protects lower portion of chain cover from wearing due to dragging in the soil.
Formed rear deflector with springs	Forming gives deflector additional strength. Springs allow deflector to "bounce" when obstructions are hit.
Rear gate down pressure springs (optional)	Forces the rear gate down to level even better. Easy-to-adjust chain tightener cast iron chain tightener is a simple bolt adjustment to keep constant tension on the chain.
Four or six tines per flange	Six tines go through the ground better than four.
"C" Tines	C Tines take less horsepower to move through the ground.
Rotor swing diameter	(RTA2570 Model = 17" [43 cm]) And (RTA3576 Model = 19" [48 cm]) For deep tilling action and turning the soil over faster.
Double lip seal on rotor bearings	Double lip seal helps keep the dirt out and the grease in.
Cat. 3 driveline with slip-clutch protection	Heavy driveline for rough conditions. Slip-clutch protects other drivetrain components and saves having to replace shear bolts.
#100 Drive chain enclosed in oil bath	Heavy-duty drive chain reduces stretching, oil keeps constant lubrication and holds wear to a minimum.
Stamped chain cover	Stamped forming adds additional strength.